NBSIR 86-330

# STOVE: A Predictive Model for Heat Transfer From Solid-Fuel Appliances

Richard D. Peacock
Richard A. Dipert

U.S. DEPARTMENT OF COMMERCE

NATIONAL BUREAU OF STANDARDS

NBSIR 86-3300

# STOVE: A PREDICTIVE MODEL FOR HEAT TRANSFER FROM SOLID-FUEL APPLIANCES

Richard D. Peacock
Richard A. Dipert

U.S. DEPARTMENT OF COMMERCE
National Bureau of Standards
National Engineering Laboratory
Center for Fire Research
Gaithersburg, MD 20899

February 1987

# TABLE OF CONTENTS

# LIST OF TABLES

# LIST OF FIGURES

# NOMENCLATURE

| | | |
|---|---|---|
| $F_{dA}$ | radiant exchange configuration factor | dimensionless |
| $F_{12}$ | radiant exchange configuration factor | dimensionless |
| h | convection heat transfer coefficient | $kW / m^2 \cdot K$ |
| k | thermal conductivity | $kW / m \cdot K$ |
| L | characteristic length | m |
| Nu | Nusselt number | dimensionless |
| Pr | Prandtl number | dimensionless |
| $R_i$ | thermal resistance | $m^2 \cdot K / kW$ |
| Ra | Raleigh number | dimensionless |
| $R_{TOTAL}$ | total thermal resistance $= \Sigma R_i$ | $m^2 \cdot K / kW$ |
| $\dot{q}$ | heat transfer rate | $kW/m^2$ |
| T | temperature | K |
| X | characteristic horizontal dimension | m |
| Y | characteristic vertical dimension | m |
| $\epsilon$ | emissivity | dimensionless |
| $\sigma$ | Stephan-Boltzmann constant | $kW / m^2 \cdot K^4$ |

# STOVE: A Predictive Model for Heat Transfer
## From Solid Fuel Appliances

Richard D. Peacock and Richard A. Dipert

## Abstract

A computer implementation of a model to predict temperatures on wall and wall protector surfaces exposed to the heating of an appliance such as a solid fuel heating appliance is described. A steady state heat transfer model with flexibility to describe a generalized method of protection for a combustible wall surface is presented along with a computer program implementing the model.

Good agreement was found comparing the model predictions with data previously collected during full scale experiments conducted to evaluate the effectiveness of generic methods of wall protection in reducing temperatures on combustible wall surfaces.

Extensive references of research related to solid fuel heating safety are included.

Key words: Chimneys; fire models; fire safety; fire tests; flues; heat transfer; heating equipment; literature reviews; radiant energy; stoves; wood.

## 1. INTRODUCTION

The U.S. Consumer Product Safety Commission and the U.S. Department of Energy, as part of a program to investigate safety risks involved with the use of solid fuel burning appliances, have sponsored experimental research at the Center for Fire Research (CFR) at the National Bureau of Standards (NBS) to identify hazards associated with solid fuel heating. The studies were conducted to provide information to improve safety practices for the use of the

appliances, and to provide data upon which to base improved codes and standards.

During the first years of the program, an accident survey, literature review, and codes and standards analysis were performed to establish accident patterns, to determine the types of risks involved with the use of wood burning appliances. and to ascertain the adequacy of existing codes and standards in addressing these risks [1-3].[1] Overwhelmingly, conditions related to installation, operation, and maintenance were responsible for the fire incidents studied. Only a small percentage of the fires was attributed to product design or product defects. Thus, safe installation and use of wood burning appliances is a critical requirement for preventing fire accidents involving the equipment. Much of the criteria for the installation and use of wood burning appliances are based upon data developed over forty years ago and do not provide information on materials of construction, or appliances available in the current market.

The present program at CFR includes research on:

- clearances to combustibles from appliances and chimney connectors [4];

- methods of protection to allow reduced clearances to walls and

---

[1]       Number in brackets refer to literature references listed in
          section 8 at the end of this report.

ceiling surfaces exposed to radiant heating by appliances and chimney connectors [5];

• temperatures developed in and around fireplaces with and without fireplace inserts installed [6,7];

• intensity and duration of chimney fires in factory-built and masonry chimneys [8];

• temperatures on combustible material surrounding chimney connectors passing through walls and / or connecting to chimneys [9], and;

• prediction of temperatures on surfaces of combustible walls exposed to heating from a typical radiant heating appliance.

This report, one of a series of reports providing information from the experimental program on wood burning safety at NBS, presents the results of the development of a computer based implementation of a model to predict temperatures on a wall surface exposed to heating from a radiant heating appliance such as a wood stove. The resulting computer program allows the user to specify thermal protection to reduce temperatures on the wall surface.

## 2.  REVIEW OF PREVIOUS WORK

### 2.1  Fire Incidents Involving Wood Burning Appliances

Recent statistics on fires and injuries related to wood burning appliances are alarming:

| Year | Fires | Change From Previous Year | Deaths | Dollar Loss |
|------|-------|---------------------------|--------|-------------|
| 1978 | 66,800  |        | 250 | $134 million |
| 1979 | 70,700  | +14%   | 210 | $175 million |
| 1980 | 112,000 | +58%   | 350 | -- |
| 1981 | 130,100 | +16%   | 290 | $265 million |
| 1982 | 139,800 | +7%    | 250 | $257 million |
| 1983 | 140,600 | +0.6%  | 280 | $296 million |

Source:  U.S. Consumer Product Safety Commission [10, 11]

There were more fires in solid fuel burning equipment, and a larger percentage increase over previous years, than were reported for any other kind of heating equipment -- including gas, electric, and oil burning appliances [10-11].

This marked increase is attributed to the growing installation and use of wood burning stoves in homes throughout the United States and the fact that most homes are made of combustible construction.  Clearly, accidental fires from wood burning appliances are an increasingly important problem.

## 2.2  Clearances in Existing Codes and Standards

Recommendations for minimum acceptable clearances to combustible materials for the installation of chimney, chimney connectors, and appliances are specified in the various model building codes and recommended practices manuals.  Reference [12] is typical of the specifications found in the codes. For simplicity, a single, hopefully conservative clearance is given for each type of appliance installed without protection.  No allowance is made for the size, heat output, heat transfer characteristics or other features unique to individual models.  Similarly, only a few, specific methods of protection employed to allow reduction of these clearances are recommended.

Typically, 0.91 m of clearance is specified between radiant heaters and unprotected combustible construction.  For residential solid fuel chimneys, typically 51 mm of clearance is required.  Chimney connectors for solid fuel burning residential appliances require a clearance of at least 0.46 m to combustible materials.  However, as with appliances, these clearances may be reduced by the use of appropriate protection applied either to the appliance or to the combustible surface.

The experimental basis for these code requirements is not, in many cases, quite so clear.  Several experimental studies have been carried out to determine minimum acceptable clearances to combustible materials.  Voigt [13], in a 1933 publication, recommends a minimum clearance of 0.30 m for chimney connectors 0.23 m in diameter.  A more extensive study, performed by Underwriters Laboratories in 1943 [14], presents minimum safe clearances for

both unprotected surfaces and surfaces protected by various methods.
Distances at which a maximum temperature rise of 50°C above room temperature
is reached are presented as a function of the temperature of the exposed face
of a heat producing appliance.  The relative protection afforded by various
materials used as heat barriers between the appliance and combustible surfaces
is also examined.  Lawson, Fox, and Webster [15] and Lawson and Simms [16]
have studied the heating of wall panels and wood by radiation.  With
experimentation and theoretical predictions, they present safe clearances
between flue pipes and wall surfaces as a function of the pipe diameter and
the pipe surface temperature.  To maintain a maximum wall temperature of
100°C, 0.15 m pipe should not exceed 350°C in surface temperature at a
clearance of 0.46 m [15].  Loftus and Peacock [5] present the results of
research studying clearances and methods of protection for wall and ceiling
surfaces exposed to radiant heating appliances.  A number of recommended
methods of protection to reduce temperatures on combustible wall and ceiling
surfaces to acceptable levels were found.  In the study, appliance surface
temperatures from 300 to 450°C were used.

These experimental studies established limits for two important para-
meters: appliance surface temperature and clearance to combustibles for
unprotected and protected surfaces.  Maximum appliance surface temperatures
for the appliances studied ranged from 300 to 450°C; average appliance surface
temperatures from 200 to 250°C.  Minimum safe wall clearances for unprotected
surfaces ranged from 0.31 to 0.91 m.  Most of the current code provisions are
only adequate for maximum appliance surface temperatures up to 300 to 350°C.

## 2.3 Temperatures Developed in Heating Systems

Tests made with prefabricated porcelain-enameled metal chimneys for solid or liquid fuel furnaces [17,18] established a limiting temperature rise of 190°C on the outer surface of the chimney for a flue gas temperature of 537°C. With this limitation, wood framing space 51 mm or more away from the chimney was considered safe. Satisfactory insulation of the chimneys to reduce the outer surface temperatures to acceptable levels was obtained with asbestos paper plies totalling about 45 mm in thickness. In the same study, some asbestos cement pipe coverings were also found to reduce heat transmission to the extent required for safety of nearby combustibles.

To establish performance requirements for lightweight prefabricated chimneys, tests were conducted with lined and unlined masonry chimneys having 102 mm thick walls [19,20]. Hazardous conditions on wood framing spaced 51 mm away from the chimney were noted with a continuous flue gas temperature of 482°C for the unlined chimney and 592°C for the lined chimney. However, these hazardous conditions were not reached in the lined chimney tests until after 13 hours. In order to study operating conditions with typical fuels, a number of firing tests [21] were conducted with heating appliances known to give high flue gas temperatures, using wood and soft coals as fuels. With a coal-fired, jacketed type heater, gas temperatures ranging from 648 to 704°C were measured for an hour or more in the flue at the ceiling level above the heater.

Lawson, Fox, and Webster [15] presented results of tests to measure surface temperature of flue pipes. Measured for a variety of flue systems using solid fuels -- mostly coal and coke -- they report temperatures of about 150°C under "normal" conditions and temperatures as high as 815°C for over fire conditions.

Fox and Whittaker [21] report temperatures on metal flues of several heating appliances operated over a range likely to encountered in normal use. Maximum flue pipe surface temperatures ranged from 704 to 815°C at the appliance flue outlet, 360 to 510°C at a distance of 0.91 m from the appliance flue outlet, and 287 to 326°C at a distance of 1.8 m from the appliance flue outlet.

Shoub [17] concluded that combustible materials will be ignited if maintained in continued contact with a masonry chimney of 120 mm wall thickness with flue gas temperatures of 400°C.

In tests for the Department of Energy [4], temperatures ranging from 297 to 436°C during normal operation and 377 to 693°C during over fire conditions were noted on the surfaces of several wood burning appliances when tested to prescribed test methods [22]. A total of 11 different short term tests, ranging from 1.9 to 25.6 hours duration, were conducted to establish normal firing conditions in wood burning appliances [23]. An examination of the data from these tests shows spikes occurring at the beginning and end of tests and, apparently, whenever the door to the stove was opened. These sharp increases in temperature were attributed to a "high fire" in the morning and to

the rapid increase in active flaming when the door was opened for refueling the fire. The average stove surface temperature rise for normal burning ranged from 177 to 218°C, flue gases from 140 to 269°C, inner chimney wall surface 119 to 241°C, and the outer chimney wall surface 14 to 48°C.

## 2.4 Limiting Safe Temperatures on Combustible Surfaces

Listings of heat producing appliances and methods for setting clearances between appliances and combustible surfaces are based upon Underwriters Laboratories listings [22]:

- maximum temperature rise of 65°C above room temperature on exposed surfaces; and
- maximum temperature rise of 50°C above room temperature on unexposed surfaces, such as beneath the appliance, floor protector, or wall mounted protective device.

These requirements are based upon the fact that while the ignition temperature of wood products is generally quoted to be on the order of 200°C [24], wood that is exposed to constant heating over a period of time may undergo a chemical change resulting in a much lowered ignition temperature and increased potential for self-ignition.

Mitchell [25] presents data on wood fiberboard exposed to temperatures as low as 109°C that resulted in ignition after prolonged exposure. MacLean

[26,27] reports charring of wood samples at temperatures as low as 93°C. He concludes that wood should not be exposed to temperatures appreciably higher than 66°C for long periods. McGuire [28] suggests that the maximum safe temperatures on the surface of a combustible material adjacent to a constant heat source should be no more than 100°C.

Clearly, the ignition of wood at moderately elevated temperatures is a complex phenomenon; the time of exposure is indeed an important parameter [29,30]. While exact limits recommended in the literature vary due to exposure time and details of the tests conducted, the numerous documented fires involving the ignition of wood members near low pressure steam pipes [31] suggest an upper temperature limit for wood exposed to long-term low-level heating should not be appreciably higher than 100°C.

Nearby combustible materials other than wall and ceiling surfaces, such as chairs or draperies must also be kept a sufficient distance from combustible materials to prevent ignition of the materials. The testing standards and model codes treat all combustibles with the same requirements. Thus, the 0.91 m clearance requirements in NFPA 211 and maximum temperature rise requirements in the Underwriters Laboratories testing standards apply equally well to other combustibles as well. Similarly, a temperature limit of 100°C is more than adequate to protect most combustibles used in furnishings.

## 2.5  Data for Model Validation

Much of the available literature related to wood heating safety provides a significant amount of data that can be used to compare theoretical predictions with experimental measurements.  In the above literature, references [4], [5], and [9] provide measurements of appliance surface temperatures and wall surface temperatures and provide a full description of the experimental setup to be modeled.  Reference [22] provides acceptable limits on combustible surface temperatures for use in predicting minimum clearances, maximum appliance surface temperatures, minimum acceptable protector thermal properties, and the like.  These references will provide the majority of data for the comparison of theoretical predictions with measured temperatures on surfaces of appliances, on protector systems, and on combustible walls.

## 3.  THEORETICAL BASIS FOR THE MODEL

Figure 1 presents a schematic diagram of a heating appliance / wall system with an arbitrary protection system between the appliance and the wall.  Heat transfers from the hot stove surface through any intervening protection to the wall surface, through the wall, and to the cooler surroundings.  A few assumptions, reasonable to the system being modeled, simplify the model considerably:

- The stove is operating at steady state conditions (thus, we assume the stove has been operating for a period of time and has reached a steady operating condition).

- Stove is at a constant uniform surface temperature.

- Heat transfer through air spaces in the system takes place by radiation and convection only.

- Heat transfer through solids in the system takes place by conduction only.

With these assumptions, a one-dimensional, steady state model of the stove / protector / wall heat transfer is appropriate. The only loss in generality of the predictive capability of the model is the inability to predict any time dependent behavior of the system. Since the intended purpose of the model is to study the fire safety of the stove / protector / wall system under worst case conditions, this loss is acceptable. By assuming steady state conditions with a constant stove temperature, the worst case conditions will be modeled.

## 3.1  Radiative Heat Transfer

For heat exchange between two surfaces, the net radiative heat transfer between surfaces 1 and 2 is given by [32]:

$$\dot{q} = \frac{\sigma \ (T_1^4 - T_2^4)}{\dfrac{1 - \epsilon_1}{\epsilon_1} + \dfrac{1}{F_{12}} + \dfrac{1 - \epsilon_2}{\epsilon_2}} \tag{1}$$

$F_{12}$, the configuration factor for radiative exchange between surface 1 and surface 2, is defined as the fraction of the radiation leaving surface 1 which is intercepted by surface 2. Compilations of configuration factors are available in the literature [33,34]. For the stove / wall protector geometry, the following equations are appropriate. The configuration factor for a differential element to a plane parallel rectangle with the normal to the element passing through the corner of the rectangle is given by [33]:

$$F_{dA} = \frac{1}{2\pi} \left[ \frac{X}{(1+X^2)^{\frac{1}{2}}} \ \tan^{-1} \frac{Y}{(1+X^2)^{\frac{1}{2}}} + \right.$$

$$\left. \frac{Y}{(1+Y^2)^{\frac{1}{2}}} \ \tan^{-1} \frac{X}{(1+Y^2)^{\frac{1}{2}}} \right] \tag{2}$$

where X = (width of rectangle) / (distance from rectangle to element) and Y = (height of rectangle) / (distance from rectangle to element). Since the configuration factor for a surface equals the sum of configuration factors for any subdivision of the surface, the configuration factor for any point $(X_w, Y_w)$ on the wall (or first protector) surface can be defined from equation (2) as

$$F_{12} = F_{dA}(X_W-X_S, Y_W-Y_S) - F_{dA}(X_W-X_S-W_S, Y_W-Y_S) +$$

$$F_{dA}(X_W-X_S-W_S, Y_W-Y_S-H_S) - F_{dA}(X_W-X_S, Y_W-Y_S-H_S) \qquad (3)$$

For radiant heat exchange between two identical, directly opposed rectangles (such as two protective surfaces of the same size), the configuration factor is given by [33]

$$F_{12} = \frac{2}{\pi XY} \left[ \ln \left[ \frac{(1+X^2)(1+Y^2)}{1+X^2+Y^2} \right]^{\frac{1}{2}} + X(1+Y^2)^{\frac{1}{2}} \tan^{-1} \frac{X}{(1+Y^2)^{\frac{1}{2}}} \right.$$

$$\left. + Y(1+X^2)^{\frac{1}{2}} \tan^{-1} \frac{Y}{(1+X^2)^{\frac{1}{2}}} - X \tan^{-1} X - Y \tan^{-1} Y \right] \qquad (4)$$

## 3.2 Convective Heat Transfer

For convective heat transfer between two surfaces separated by an air space, the net heat exchange by convection is given by

$$\dot{q} = h (T_1 - T_2) \qquad (5)$$

where h is the convective heat transfer coefficient. For free convection at

the surface of a vertical surface (such as the wall, appliance, or protector surface), h can be found from the equations [35]

$$Nu_L = \frac{h\,L}{k} = \left[ 0.825 + \frac{0.387\ Ra_L^{1/6}}{\left[ 1 + (0.492/Pr)^{9/16} \right]^{8/27}} \right]^2 \tag{6}$$

### 3.3 Conductive Heat Transfer

For solids, the net heat exchange by conduction is given by

$$\dot{q} = \frac{k}{L}\,(T_1 - T_2) \tag{7}$$

While for some materials, the thermal conductivity, k, is a function of temperature, for most materials, the assumption that k is a constant leads to inconsequential loss in generality.  For instance, for aluminum, the thermal conductivity changes by only 25% over a temperature range from -170°C to well over 2000°C

## 3.4  Solution of the Equations for an Arbitrary Protection System

At steady state, the heat transferred from the appliance to the outside, figure 2, is equal to the heat transferred through any element or group of elements within the system, or

$$\dot{q}_{TOTAL} = \frac{(T_S - T_O)}{R_{TOTAL}} = \dot{q}_i = \frac{(T_i - T_{i+1})}{R_i} \tag{8}$$

Equations (1), (5), and (7) can be expressed as in equivalent resistance forms as

$$\text{(Conduction)} \qquad R_i = \frac{L}{K} \tag{9}$$

$$\text{(Convection)} \qquad R_i = \frac{1}{h} \tag{10}$$

$$\text{(Radiation)} \qquad R_i = \frac{\dfrac{1 - \epsilon_1}{\epsilon_1} + \dfrac{1}{F_{12}} + \dfrac{1 - \epsilon_2}{\epsilon_2}}{\sigma (T_1^2 + T_2^2)(T_1 + T_2)} \tag{11}$$

For the current problem, these equations can be combined into two as

$$\text{(Solids)} \qquad R_i = \frac{L}{K} \tag{12}$$

$$\text{(Airspaces)} \quad R_i = \cfrac{1}{\cfrac{1}{h} + \cfrac{\sigma (T_1^2 + T_2^2)(T_1 + T_2)}{\cfrac{1 - \epsilon_1}{\epsilon_1} + \cfrac{1}{F_{12}} + \cfrac{1 - \epsilon_2}{\epsilon_2}}} \qquad (13)$$

Thus, the solution method with a given appliance temperature, $T_S$, and a given temperature of the surroundings, $T_0$, begins by assuming temperatures for the intermediate surfaces, calculating individual resistances from equations (12) and (13) to determine the total resistance, $R_{TOTAL}$, calculating the total heat flow rate from equation (8), and comparing the total heat flow rate to the individual heats. If the calculated individual rates are sufficiently close to the calculated total heat flow rate, the steady state solution has been obtained. If any of the individual heats are different from the total heat, new estimates for each of the intermediate temperatures are made and the process is repeated until sufficient agreement has been found. Reference [36] provides a number of methods for making best guess estimates for the next iteration toward the solution. For the current problem, a simple linear search is used where one variable at a time is changed until a local optimum is found.

A number of literature sources are available to allow determination of the physical data required for the input (for instance, for the thermal conductivity and emissivity). References [32] and [33] provide extensive listings of thermal and material properties for common materials.

## 4. COMPUTER IMPLEMENTATION OF THE MODEL

Included as Appendix A is a listing of the FORTRAN (written in ANSI standard FORTRAN 77) program implementing the model as described above. The general structure of the program is illustrated in figure 3.

Program input (detailed in Appendix B) takes the form of different key words with arguments to specify values which depend upon the key word. In most cases, the order of the key words is unimportant. A description of each of the input key words and values which go on the same line are presented below:

```
STOVE        <height> <width> <emissivity> <temperature>
AIRSPACE     <thickness> <emissivity>
FOR          <variable> = <lower> <upper> <increment>
XWALL        <x position>
YWALL        <y position>
PROTECTOR    <thickness> <height> <width> <k> <emissivity> <temperature>
```

A sample input for the program follows:

```
FOR:              TSTOVE = 473.15 673.15 10.
STOVE:            0.9 0.5 0.5 473.15
AIRSPACE:         0.91 0.9
ALUMINUM SHEET:   0.00254 3.0 3.0 177. 0.9
AIRSPACE:         0.0254 0.9
ALUMINUM SHEET:   0.00254 3.0 3.0 177. 0.9
AIRSPACE:         0.0254 0.9
GYPSUM WALLBOARD: 0.0127 3.0 3.0 0.17 0.9
F/G INSULATION:   0.0916 3.0 3.0 0.038 0.9
BRICK OUTSIDE:    0.0916 3.0 3.0 0.72 0.9
AIRSPACE:         273.15
END:
```

This input specifies a series of calculations to be done for a stove temperature ranging from 200°C to 400°C ( 473.15 to 673.15 K in the input above) for a wall protection system consisting of two aluminum sheets spaced 25 mm (0.00254 m in the input above) apart and placed 25 mm from an insulated outside wall of a house. A clearance of 0.91 m from the appliance to the first aluminum sheet is specified. A sample output from the program, using this sample data set, is presented in table 1. Calculated temperatures on all surfaces from the stove to the outdoors are shown along with the specified sizes and thermal properties of the materials used for the walls and protectors. Execution time, of course, depends upon the computer in use. On a typical desk top personal computer, execution of the above test case required less than 1.5 minutes.

## 5. COMPARISON OF THE MODEL PREDICTIONS WITH EXPERIMENTAL DATA

Figure 4 presents a comparison of calculated temperatures on the surfaces of wall protectors and on the surfaces of combustible walls with experimentally measured values taken from references [4] and [5]. To assess the predictive capabilities of the model, a range of conditions from the experimental studies were simulated. Wall materials used in these experimental studies ranged from uninsulated gypsum wallboard to a fully insulated stud wall with a brick facing on the exterior. A number of different wall protection methods were taken from reference [5], varying from a simple sheet metal protector to a sheet metal / insulation board / air space composite protector or a ventilated brick protector. A simple cross plot of

the calculated values and the experimental values illustrates the agreement of the model's predictions with experimental data obtained in earlier studies. Agreement of the calculated values with the experimentally measured values, stated as

$$( ( T_{calculated} - T_{measured} ) / T_{calculated} ) * 100$$

with temperatures expressed in absolute, averaged within less than 1 percent. Individual agreement, however ranged from 5 percent low (calculated values lower than experimental) to 4 percent high. Much of the disparity in the comparison can be explained by the choice of ambient conditions for the experimental tests. All the data in the two reports were described in terms of temperature rise above ambient conditions. Since the experimental calculations are based upon absolute temperatures, some assumptions had to be made for the ambient temperatures in the surroundings during the tests. A variation in ambient temperature of 15°C could change the calculated surface temperatures on the wall surfaces by as much as ±10 percent. Thus, the agreement illustrated in figure 5 is excellent in light of the possible variation in the calculations depending upon the assumed ambient temperature.

## 6. MODEL CAPABILITIES AND EXAMPLES

A theoretical model for predicting the heat transfer between the appliance and the wall surfaces can be a useful tool not only in the design of appliances and wall protection devices but also in the design of future experiments to study clearances and reduced clearances for wood burning

appliances. This section presents some examples of the use of the model in predicting temperatures and clearances from combustibles for both protected and unprotected wall surfaces.

## 6.1 Heat Transfer From Appliance to an Unprotected Wall

Figure 5 shows calculated wall surface temperatures as a function of appliance / wall clearance for a medium size appliance (an appliance 0.5 by 0.5 m on the side parallel to the wall surface) adjacent to an unprotected wall surface for appliance surface temperatures from 150 to 350°C. For these calculations, the outside air temperature (temperature of the surroundings) was assumed equal to 0°C. The wall consisted of 12 mm gypsum wallboard, a 92 mm stud space with glass fiber insulation, and a 92 mm common brick facing on the outside of the wall exposed to the outdoors. At an appliance clearance of 0.91 m, appliance surface temperatures greater than about 300 °C would lead to temperatures on the wall in excess of the recommended limit [22] of 50°C above room ambient temperature at a point on the wall directly centered behind the appliance. Since, in an earlier study [4], average appliance surface temperatures of about 200 °C were noted, a sufficient margin of safety is indicated for an appliance this size.

## 6.2  Heat Transfer From Appliance to a Sheet Metal Protected Wall

Figures 6 and 7 show calculated wall surface temperatures as a function of appliance / wall clearance for a medium size appliance (an appliance 0.5 by 0.5 m on the side parallel to the wall surface) adjacent to a protected wall surface for appliance surface temperatures from 150 to 350°C.  As before, the outside air temperature was assumed equal to 0°C.  The wall protector consisted of two sheets of aluminum (2.5 mm in thickness) separated by a ventilated 25 mm air space.  The wall protector was spaced from the wall by a ventilated 25 mm air space.  The wall consisted of 12 mm gypsum wallboard, a 92 mm stud space with glass fiber insulation, and a 92 mm common brick facing on the outside of the wall exposed to the outdoors.  With the surfaces of the protector painted black and at an appliance clearance of 0.91 m, appliance surface temperatures greater than about 300°C would lead to temperatures on the wall in excess of the recommended limit of 50°C above room ambient temperature -- in fact, about the same as the case with no protection. However, when the surfaces of the protector are left unpainted (shiny aluminum surfaces), appliance surface temperatures higher than 350°C are required to raise the temperature of the wall surface above acceptable limits. Conversely, the clearance of the appliance to the wall could be reduced from 0.91 m to 0.3 m with an average appliance surface temperature of 200°C.

## 6.3 Heat Transfer From Appliance to a Masonry Protected Wall

Figure 8 shows calculated wall surface temperatures as a function of appliance / wall clearance for the same appliance (an appliance 0.5 by 0.5 m on the side parallel to the wall surface) adjacent to a protected wall surface for appliance surface temperatures from 150 to 350°C. Again, the outside air temperature was assumed equal to 0°C. The wall protector consisted of a 92 mm thick solid brick wall was spaced from the wall by a ventilated 25 mm air space. The wall consisted of 12 mm gypsum wallboard, a 92 mm stud space with glass fiber insulation, and a 92 mm common brick facing on the outside of the wall exposed to the outdoors. With the surfaces of the protector painted black and at an appliance clearance of 0.91 m, appliance surface temperatures greater than about 300°C would lead to temperatures on the wall in excess of the recommended limit of 50°C above room ambient temperature -- again not significantly lower than in wall surface temperatures than for the unprotected wall. Note, however, one of the major thermal characteristics of a masonry wall protection system -- high thermal mass -- is not accounted for in a steady state prediction.

## 7. USES FOR AND LIMITATIONS OF THE MODEL

A model was developed to predict temperatures on protected and unprotected wall surfaces exposed to heating from a (primarily) radiant heating appliance. A one-dimensional, steady state model of appliance / protector / wall heat transfer showed agreement within an average of less than 1 percent

when compared to experimental results from earlier laboratory studies. A range of building materials typical of residential construction, along with a number of different wall protection methods were simulated in the comparison. As a guideline to the range of applicability of the model, the variations of the thermal properties used in the comparisons were

| | | | | |
|---|---|---|---|---|
| k: | 0.038 | to | 177 | W/m · K |
| $\epsilon$: | 0.1 | to | 0.9 | |
| airspace thickness: | 0.1 | to | 1.0 | m |
| solid thickness: | 0.0025 | to | 0.1 | m |

Improvements in the program implementation of the model are possible. The simple linear search for the solution of the equations is certainly not the most efficient method. A number of search methods have been described in the literature [36]. An n-dimensional simplex search where the next guess for a given variable depends upon the values of the other n-1 variables would improve the execution speed of the program. Additional improvements would be realized with any of a number of acceleration methods, also available in the literature [36]. Of course, a more complicated, harder to understand and modify program would result.

# 8. REFERENCES

[1]    Peacock, R. D., A Review of Fire Incidents, Model Building Codes, and Standards Related to Wood-Burning Appliances, Nat. Bur. Stand. (U.S.), NBSIR 79-1731 (April 1979).

[2]    Peacock, R. D., A Review of Fire Incidents Related to Wood-Burning Appliances, Wood Energy Institute, Proceedings of Wood Heating Seminar IV, Portland, Oregon, March 21-24, 1979, 43-46.

[3]    Shelton, J. W., Analysis of Fire Reports on File in the Massachusetts State Fire Marshal's Office Relating to Wood and Coal Heating Equipment, contract to the National Bureau of Standards (U.S.), NBSGCR 78-149 (November 1978).

[4]    Peacock, R. D., Ruiz, E., and Torres-Pereira, R., Fire Safety of Wood Burning Appliances, Part 1:  State of the Art Review and Fire Tests, Volume I and II, Nat. Bur. Stand. (U.S.), NBSIR 80-2140 (November 1980).

[5]    Loftus, J. J., and Peacock, R. D., Clearances and Methods of Protection for Wall and Ceiling Surfaces Exposed to Radiant Heating Appliances, Nat. Bur. Stand. (U.S.), NBSTN 1205 (December 1984).

[6]    Maxwell, T. T., Dyer, D. F., Maples, G., and Burch, T., An Investigation of Creosoting and Fireplace Inserts, contract to the National Bureau of Standards (U.S.), NBSGCR 81-365 (December 1981).

[7]    Terpstra, W. R., Jorgenson, M. L., and Dosedlo, L. J., Investigation of Fire Hazards of Fireplace Inserts in Factory-Built and Masonry Fireplaces, contract to the National Bureau of Standards (U.S.), NBSGCR 82-368 (January 1982).

[8]    Peacock, R. D., Intensity and Duration of Chimney Fires in Several Chimneys, Nat. Bur. Stand. (U.S.), NBSIR 83-2771 (December 1983).

[9]    Loftus, J. J., and Peacock, R. D., Evaluation of Thimble - Chimney Connector (Wall-Pass Through) Systems for Solid Fuel Burning Appliances, Nat. Bur. Stand. (U.S.), NBSIR 84-2969 (November 1984).

[10]   Kale, D., Fires in Woodburning Appliances, U. S. Consumer Product Safety Commission (December 1982).

[11]   Harwood, B., and Kale, D., Fires Involving Fireplaces, Chimneys and Related Appliances, U. S. Consumer Product Safety Commission (September 1981).

[12]   Standard for Chimneys, Fireplaces, Vents and Solid Fuel Burning Appliances, NFPA 211-1984, National Fire Protection Association, Quincy, Massachusetts (February 1984).

[13]  Voigt, G. Q., Fire Hazard of Domestic Heating Installations,
      Nat. Bur. Stand. (U.S.), NBS Research Paper RP596 (September 1933).

[14]  Neale, J. A., Clearances and Insulation of Heating Appliances, Under-
      writers Laboratories, Inc., UL Bulletin of Research No. 27 (February
      1943).

[15]  Lawson, D. I., Fox, L. L., and Webster, C. T., The Heating of Panels by
      Flue Pipes, Fire Research Special Report No. 1, Fire Protection Associa-
      tion, London, England  (March 1952).

[16]  Lawson, D. I., and Simms, D. L., The Ignition of Wood by Radiation,
      British Journal of Applied Physics, Vol 3, 288-292 (September 1952).

[17]  Shoub, H., Survey of Literature on the Safety of Residential Chimneys
      and Fireplaces, Nat. Bur. Stand. (U.S.), NBS Misc. Pub. 252 (December
      1963).

[18]  Prefabricated Metal Chimneys, National Bureau of Standards, Fire
      Research Section, unpublished reports to the Federal Public Housing
      Authority (1941-1945).

[19]  Thulman, R. K., Temperatures Developed in Chimneys for Low Cost Houses,
      Nat. Bur. Stand. (U.S.), Tech. News. Bull. 328 (August 1944).

[20]  Thulman, R. K., Performance of Masonry Chimneys for Houses, Housing and
      Home Finance Agency (U. S.), Housing Research Paper No. 13 (November
      1952).

[21]  Fox., L. L., and Whittaker, D., Some Measurements of Temperatures of
      Metal Flues of Domestic Heating Appliances, Journal of the Institution
      of Heating and Ventilation Engineers, Vol. 23, 183-192 (August 1955).

[22]  Standard for Room Heaters, Solid Fuel Type -- UL 1482, First Edition,
      Underwriters Laboratories, Inc., Northbrook, IL (August 1979).

[23]  Loftus, J. J., Evaluation Tests on Metal Factory-Built Insulated
      Chimneys Used for Venting Solid Fuel Burning Appliances,
      Nat. Bur. Stand. (U.S.), letter report to the U. S. Consumer Product
      Safety Commission (April 1985).

[24]  Schaffer, E. L., Smoldering Initiation in Cellulosics Under Prolonged
      Heating, Fire Technology, Vol. 16, No. 1, 22-28 (February 1980).

[25]  Mitchell, N. D., New Light on Self-Ignition, NFPA Quarterly, Vol. 45,
      No. 2, 165-172 (October, 1951).

[26]  Maclean, J. D., Effect of Heat on Properties and Serviceability of
      Wood:  Experiments on Thin Wood Specimens, Forest Products Laboratory
      Report No. R1471, Madison, WI (1945).

[27]  Maclean, J. D., Rate of Disintegration of Wood Under Different Heating
      Conditions, American Wood-Preservers Association (1951).

[28]  McGuire, J. H., Limiting Safe Temperature of Combustible Materials, Fire
      Technology, Vol 5, No. 3 (August 1969).

[29]  Ignition and Charring Temperatures of Wood, Forest Products Laboratory
      Report No. 1464, Madison, WI  (January 1958).

[30]  Shelton, J. W., Wood Heat Safety, Garden Way Publishing, Charlotte, VT
      (September 1979).

[31]  Matson, A. F., Dufori, R. E., and Breen, J. F., Performance of Type B
      Gas Vents for Gas-Fired Appliances, Part II, Survey of Available
      Information on Ignition of Wood Exposed to Moderately Elevated Tempera-
      tures, Underwriters Laboratories, Inc., UL Bulletin of Research No. 51,
      Northbrook, IL (May 1959).

[32]  Incorpera, F. P., and DeWitt, D. P., Fundamentals of Heat Transfer, John
      Wiley & Sons, New York, NY (1981).

[33]  Siegel, R., and Howell, J. R., Thermal Radiation Heat Transfer, McGraw-
      Hill Book Company, New York, NY (1981).

[34]  Hsu, Chia-Jung, Shape Factor Equations for Radiant Heat Transfer Between
      Two Arbitrary Sizes of Rectangular Planes, Canadian Journal of Chemical
      Engineering, Vol. 45, 58-60 (February 1967).

[35]  Churchill, S. W., and Chu, H. H. S., Correlating Equations for Laminar
      and Turbulent Free Convection from a Vertical Plate, Int. J. Heat Mass
      Transfer, Vol. 18, 1323 (1975).

[36]  Beveridge, G. S., and Schechter, R. S., Optimization:  Theory and Prac-
      tice, McGraw-Hill Book Company, New York, NY  (1970).

## Table 1. Sample Output From STOVE

DOUBLE ALUMINUM PLATE, ALL SURFACES PAINTED BLACK

NUMBER OF NODES IN CALCULATION: 10
POINT ON WALL: (X): 0.000 (Y): 0.000

SERIES OF CALCULATIONS FOR VARIABLE TSTOVE: 473.150 673.150 20.000

| I | MATERIAL | HEIGHT (m) | WIDTH (m) | THICK (m) | EMISS | K (W/m·K) | TEMPERATURE (°C) |
|---|----------|-----------|-----------|-----------|-------|-----------|------------------|
| 0 | STOVE | 0.50 | 0.50 | | 0.90 | | 200.00 |
| 1 | AIRSPACE | | | 0.91 | 0.90 | | |
| 2 | ALUMINUM SHEET | 3.00 | 3.00 | 0.00 | 0.90 | 177.000 | |
| 3 | AIRSPACE | | | 0.03 | 0.90 | | |
| 4 | ALUMINUM SHEET | 3.00 | 3.00 | 0.00 | 0.90 | 177.000 | |
| 5 | AIRSPACE | | | 0.03 | 0.90 | | |
| 6 | GYPSUM WALLBOARD | 3.00 | 3.00 | 0.01 | 0.90 | 0.170 | |
| 7 | INSULATION | 3.00 | 3.00 | 0.09 | 0.90 | 0.038 | |
| 8 | BRICK OUTSIDE | 3.00 | 3.00 | 0.09 | 0.90 | 0.720 | |
| 9 | AIRSPACE | | | 0.00 | 1.00 | | 0.00 |

```
   0:   STOVE / AIRSPACE
   1:   AIRSPACE / ALUMINUM SHEET
   2:   ALUMINUM SHEET / AIRSPACE
   3:   AIRSPACE / ALUMINUM SHEET
   4:   ALUMINUM SHEET / AIRSPACE
   5:   AIRSPACE / GYPSUM WALLBOARD
   6:   GYPSUM WALLBOARD / INSULATION
   7:   INSULATION / BRICK OUTSIDE
   8:   BRICK OUTSIDE / AIRSPACE
   9:   AIRSPACE
```

| TSTOVE | ( 0) (°C) | ( 1) (°C) | ( 2) (°C) | ( 3) (°C) | ( 4) (°C) | ( 5) (°C) | ( 6) (°C) | ( 7) (°C) | ( 8) (°C) | ( 9) (°C) |
|--------|------|------|------|------|------|------|------|-----|-----|-----|
| 473.150 | 200.0 | 33.1 | 33.1 | 31.6 | 31.6 | 30.1 | 29.3 | 3.1 | 1.7 | 0.0 |
| 493.150 | 220.0 | 38.7 | 38.7 | 37.0 | 37.0 | 35.3 | 34.4 | 3.6 | 2.0 | 0.0 |
| 513.150 | 240.0 | 44.7 | 44.7 | 42.8 | 42.8 | 41.0 | 39.9 | 4.2 | 2.3 | 0.0 |
| 533.150 | 260.0 | 51.1 | 51.1 | 49.0 | 49.0 | 47.0 | 45.7 | 4.7 | 2.6 | 0.0 |
| 553.150 | 280.0 | 57.8 | 57.8 | 55.6 | 55.6 | 53.4 | 51.9 | 5.4 | 2.9 | 0.0 |
| 573.150 | 300.0 | 64.8 | 64.8 | 62.5 | 62.5 | 60.1 | 58.5 | 6.0 | 3.2 | 0.0 |
| 593.150 | 320.0 | 72.2 | 72.2 | 69.7 | 69.7 | 67.2 | 65.4 | 6.7 | 3.6 | 0.0 |
| 613.150 | 340.0 | 79.9 | 79.9 | 77.3 | 77.3 | 74.6 | 72.6 | 7.4 | 3.9 | 0.0 |
| 633.150 | 360.0 | 87.8 | 87.8 | 85.1 | 85.1 | 82.3 | 80.1 | 8.1 | 4.3 | 0.0 |
| 653.150 | 380.0 | 96.0 | 96.0 | 93.2 | 93.2 | 90.3 | 87.8 | 8.8 | 4.7 | 0.0 |
| 673.150 | 400.0 | 104.3 | 104.3 | 101.5 | 101.5 | 98.5 | 95.8 | 9.6 | 5.0 | 0.0 |

Figure 1.   Heat Transfer From Hot Appliance to Cooler Wall Surface

Figure 2. Node Model Representation of Stove / Protector / Wall System

Surroundings

Appliance and chimney

$T_i = $ surface temperature at interface of node i-1 and node i

Node i is a solid

$$\dot{q}_i = \frac{K}{L}(T_{i-1} - T_i)$$

$T_{i-1} = $ surface temperature at interface of node i-2 and node i-1

$\dot{q}$  node$_{i+1}$

node$_{i-1}$  $\dot{q}$

$T_i = $ surface temperature at interface of node i-1 and node i

Node i is an airspace

$$\dot{q}_i = h(T_{i-1} - T_i) + \frac{\sigma(T_{i-1}^4 - T_i^4)}{\frac{1-\varepsilon_{i-1}}{\varepsilon_{i-1}} + \frac{1}{F_{i-1\,i}} + \frac{1-\varepsilon_i}{\varepsilon_i}}$$

$T_{i-1} = $ surface temperature at interface of node i-2 and node i-1

$\dot{q}$  node$_{i+1}$

node$_{i-1}$  $\dot{q}$

Figure 3. Program Layout For Program STOVE

Figure 4. Comparison of Calculated Wall and Protector Surface Temperatures With Experimental Results

Figure 5.   Predicted Wall Surface Temperatures for Heat Transfer From Appliance Surface to an Unprotected Combustible Wall Surface

Figure 6.  Predicted Wall Surface Temperatures for Heat Transfer From Appliance Surface to a Combustible
Wall Protected With a Double Aluminum Sheet Wall Protector (Painted Black)

Figure 7. Predicted Wall Surface Temperatures for Heat Transfer From Appliance Surface to a Combustible Wall Protected With a Double Aluminum Sheet Wall Protector

Figure 8. Predicted Wall Surface Temperatures for Heat Transfer From Appliance Surface to a Combustible Wall Protected With a Solid Masonry Wall Protector With A Ventilated Air Space



Appliance/Wall Heat Transfer

Appliance size: 0.25 m²

Protector: Ventilated masonry wall

Wall: Gypsum wallboard
        Insulated wall
        Brick facing

Stove Temperature (°C)

350
325
300
275
250
225
200
175
150

WALL TEMPERATURE (°C)

CLEARANCE (m)

**Appendix A:    Program Listing of STOVE**

```
1  |        PROGRAM STOVE                                                       1
2  |C                                                                           2
3  |C    @@@@@@@@                                                               3
4  |C    @@@@   @        @                                                      4
5  |C    @@@@      @@@@@@    @@@@@@    @@@ @    @@@@@@                           5
6  |C    @@@@@@@@    @@@@    @@@ @    @@@ @    @ @@@                            6
7  |C        @@@@    @@@@    @@@ @    @@@ @    @@@@@@                           7
8  |C    @ @@@@    @@@@    @@@ @    @@@@    @                                  8
9  |C    @@@@@@@    @@@@    @@@@@@     @@    @@@@@@                            9
10 |C                                                                          10
11 |C                                                                          11
12 |C    THIS PROGRAMS CALCULATES AN ENERGY BALANCE ON A STOVE / WALL SYSTEM   12
13 |C    ASSUMING STEADY STATE CONDITIONS, WITH AN ARBITRARY NUMBER OF WALL    13
14 |C    PROTECTORS BETWEEN THE STOVE AND THE WALL                            14
15 |C                                                                          15
16 |        INCLUDE 'STOVE.CMN'                                                16
17 |        CHARACTER CMET*5,PMATL*60,VERSN*7                                  17
18 |        LOGICAL THRU1,NOTYET,THEEND                                        18
19 |        DATA VERSN /'86.0108'/                                             19
20 |C                                                                          20
21 |C    INITIALIZE EVERYTHING TO DEFAULT CONDITIONS, READ INPUT FOR CASE      21
22 |C                                                                          22
23 |        QEPS=0.00001                                                       23
24 |        EPS=0.0001                                                         24
25 |        TSTEP1=2.                                                          25
26 |        TSTEP2=2.                                                          26
27 |10      CALL INPUT(THEEND)                                                 27
28 |        IF (.NOT. THEEND) THEN                                             28
29 |          XSTOVE=WSTOVE/2.                                                 29
30 |          YSTOVE=0.                                                        30
31 |          IF (.NOT.FULPRT) THEN                                           31
32 |            WRITE (6,11) (I,PMATL(MATL(I),MATL(I+1)),I=0,N-1),N,MATL(N)    32
33 |            WRITE (6,12) VNAME,(I,I=0,N)                                   33
34 |            WRITE (6,8) '            ',(' (°C) ',I=0,N)                    34
35 |            WRITE (6,8) ('————————',I=-1,N)                               35
36 |          END IF                                                          36
37 |          NCALCS=MAX(INT((VUPPER-VLOWER)/VINCR+0.5)+1,1)                   37
38 |          DO 100 ICALC=1,NCALCS                                           38
39 |          VARVAL=VLOWER+VINCR*(ICALC-1)                                   39
40 |C                                                                          40
41 |C    SET NEXT VALUE OF VARIABLE TO BE INCREMENTED                          41
42 |C                                                                          42
43 |          IF (IVAR.EQ.1) THEN                                             43
44 |            XWALL=VARVAL                                                   44
45 |          ELSE IF (IVAR.EQ.2) THEN                                        45
46 |            YWALL=VARVAL                                                   46
47 |          ELSE IF (IVAR.EQ.3) THEN                                        47
48 |            T(0)=VARVAL                                                    48
49 |          ELSE IF (IVAR.EQ.4) THEN                                        49
50 |            L(ISUB)=VARVAL                                                 50
51 |            IF (ISUB.EQ.1) ZSTOVE=VARVAL                                  51
52 |          ELSE IF (IVAR.EQ.5) THEN                                        52
53 |            WIDTH(ISUB)=VARVAL                                            53
54 |            IF (ISUB.EQ.0) WSTOVE=VARVAL                                  54
55 |            XSTOVE=WSTOVE/2.                                              55
56 |          ELSE IF (IVAR.EQ.6) THEN                                        56
57 |            HEIGHT(ISUB)=VARVAL                                           57
58 |            IF (ISUB.EQ.0) HSTOVE=VARVAL                                  58
59 |          ELSE IF (IVAR.EQ.7) THEN                                        59
60 |            K(ISUB)=VARVAL                                                 60
61 |          ELSE IF (IVAR.EQ.8) THEN                                        61
62 |            EMMIS(ISUB)=VARVAL                                            62
63 |          END IF                                                          63
64 |C                                                                          64
65 |C    INITIALIZE THE COUNTERS TO ZERO                                       65
66 |C                                                                          66
67 |          ITER=0                                                          67
68 |C                                                                          68
69 |C    INITIALIZE TEMPERATURE GUESSES TO WORST CASE CONDITIONS               69
70 |C                                                                          70
```

```
71  |          DO 20 I=1,N-1                                                      |   71
72  |20        T(I)=T(N)                                                          |   72
73  |          TDIFF=T(0)-T(N)                                                    |   73
74  |          TGOAL=T(N)                                                         |   74
75  |C                                                                            |   75
76  |C    DETERMINE NEXT GUESS FOR TEMPERATURES                                   |   76
77  |C                                                                            |   77
78  |          DO 30 I=1,N-1                                                      |   78
79  |30        T(I)=T(I)+TDIFF/N                                                  |   79
80  |C                                                                            |   80
81  |C    CALCULATE TOTAL RESISTANCE AND HEAT FLOW FROM GUESSED TEMPERATURES      |   81
82  |C                                                                            |   82
83  |          CALL HEATS                                                         |   83
84  |40        INNER=0                                                            |   84
85  |C                                                                            |   85
86  |C    CALCULATE WITH NEWLY GUESSED TEMPERATURES AND HEATS                     |   86
87  |C                                                                            |   87
88  |          DO 60 I=1,N                                                        |   88
89  |          TINC=ABS(TDIFF/N/TSTEP1)                                           |   89
90  |          TINCI=TINC                                                         |   90
91  |          QSIGN=DSIGN(1.D0,Q(I)-QTOTAL)                                      |   91
92  |C                                                                            |   92
93  |C GO THROUGH INNER ITERATION LOOP AT LEAST ONCE FOR SOME FORCED              |   93
94  |C IMPROVEMENT                                                                |   94
95  |C                                                                            |   95
96  |          THRU1=.FALSE.                                                      |   96
97  |50        IF (.NOT. (ABS((Q(I)-QTOTAL)/QTOTAL).LE.QEPS.AND.THRU1)) THEN      |   97
98  |            INNER=INNER+1                                                    |   98
99  |            THRU1=.TRUE.                                                     |   99
100 |            IF (ABS((Q(I)-QTOTAL)/QTOTAL).GT.QEPS) NOTYET=.TRUE.             |  100
101 |            IF (MATL(I).NE.'AIRSPACE') THEN                                  |  101
102 |C                                                                            |  102
103 |C    HEAT TRANSFER IS CONDUCTION, CALCULATE TEMPERATURE                      |  103
104 |C                                                                            |  104
105 |              T(I)=T(I-1)-QTOTAL*R(I)                                        |  105
106 |            ELSE                                                             |  106
107 |C                                                                            |  107
108 |C    HEAT TRANSFER IS BY CONVECTION & RADIATION, SEARCH FOR TEMPERATURE      |  108
109 |C                                                                            |  109
110 |              T(I)=T(I)+QSIGN*TINC                                           |  110
111 |C                                                                            |  111
112 |C    RECALCULATE THE HEAT FLOW AND COMPARE TO TOTAL HEAT                     |  112
113 |C                                                                            |  113
114 |              CALL HEAT(I)                                                   |  114
115 |              IF (DSIGN(1.D0,Q(I)-QTOTAL).NE.QSIGN) THEN                     |  115
116 |                TINCI=TINCI/TSTEP2                                           |  116
117 |                TINC=TINCI                                                   |  117
118 |                QSIGN=DSIGN(1.D0,Q(I)-QTOTAL)                                |  118
119 |              ELSE                                                           |  119
120 |                TINC=TINC*2.                                                 |  120
121 |              END IF                                                         |  121
122 |              GO TO 50                                                       |  122
123 |            END IF                                                           |  123
124 |          END IF                                                            |  124
125 |C                                                                            |  125
126 |C    RECALCULATE TOTAL HEAT WITH THE NEW TEMPERATURES AND PROCEED            |  126
127 |C                                                                            |  127
128 |          CALL HEATS                                                         |  128
129 |60        CONTINUE                                                           |  129
130 |C                                                                            |  130
131 |C    IF DEBUG IS ON, PRINT OUT A SUMMARY OF THE ITERATION                    |  131
132 |C                                                                            |  132
133 |          ITER=ITER+1                                                        |  133
134 |          IF (DEBUG.AND.NOTYET) THEN                                         |  134
135 |            WRITE (6,7) ITER,INNER                                           |  135
136 |            WRITE (6,'(1X,A,F7.2)') 'STOVE TEMPERATURE: ',T(0)-273.15        |  136
137 |            WRITE (6,'(1X,A,F8.2,A,F8.3)') 'TOTAL HEAT: ',QTOTAL,            |  137
138 |     2                            '  TOTAL RESISTANCE: ',RTOTAL              |  138
139 |            WRITE (6,3)                                                      |  139
140 |            DO 70 I=1,N                                                      |  140
```

```
141 |          IF (MATL(I).EQ.'AIRSPACE'.AND.I.EQ.1) THEN            |  141
142 |             WRITE (6,5) MATL(I),T(I)-273.15,R(I),Q(I),CF(I)    |  142
143 |          ELSE IF (MATL(I).EQ.'AIRSPACE'.AND.I.NE.1) THEN        |  143
144 |             WRITE (6,1) MATL(I),T(I)-273.15,R(I),Q(I),H(I),CF(I)|  144
145 |          ELSE                                                   |  145
146 |             WRITE (6,2) MATL(I),T(I)-273.15,R(I),Q(I)           |  146
147 |          END IF                                                 |  147
148 |70        CONTINUE                                               |  148
149 |          TDIFF=T(N)-TGOAL                                       |  149
150 |          WRITE (6,'(1X,A7,F10.3,A)') 'TDIFF: ',TDIFF,           |  150
151 |     2                      CMET(TDIFF/TGOAL,EPS)                |  151
152 |          WRITE (6,6) 'QMET:  ',(Q(I)-QTOTAL,                    |  152
153 |     2                CMET((Q(I)-QTOTAL)/QTOTAL,EPS),I=1,N)      |  153
154 |       END IF                                                    |  154
155 |       TDIFF=T(N)-TGOAL                                          |  155
156 |       T(N)=TGOAL                                                |  156
157 |C                                                                |  157
158 |C   IF ANY OF THE INDIVIDUAL HEATS HAVEN'T CONVERGED ON THE FINAL VALUE,|  158
159 |C   CONTINUE WITH THE PROCESS UNTIL ALL ARE EQUAL               |  159
160 |C                                                                |  160
161 |       NOTYET=.FALSE.                                            |  161
162 |       DO 80 I=1,N                                               |  162
163 |       IF (ABS((Q(I)-QTOTAL)/QTOTAL).GT.EPS) NOTYET=.TRUE.       |  163
164 |80     CONTINUE                                                  |  164
165 |       IF (ABS(TDIFF)/TGOAL.GT.EPS) NOTYET=.TRUE.                |  165
166 |       IF (NOTYET) GO TO 40                                      |  166
167 |C                                                                |  167
168 |C   THE SOLUTION HAS BEEN FOUND, PRINT IT OUT                   |  168
169 |C                                                                |  169
170 |       IF (.NOT.FULPRT) THEN                                     |  170
171 |          WRITE (6,9) VARVAL,(T(I)-273.15,I=0,N)                 |  171
172 |       ELSE                                                      |  172
173 |          WRITE (6,4) TITLE                                      |  173
174 |          WRITE (6,'(1X,A,I3)') 'ITERATIONS: ',ITER             |  174
175 |          WRITE (6,'(1X,3A,F8.3)') 'VARIED VARIABLE: ',VNAME,' = ',|  175
176 |     2                             VARVAL                        |  176
177 |          WRITE (6,'(1X,A,F7.2)') 'STOVE TEMPERATURE: ',T(0)-273.15|  177
178 |          WRITE (6,'(1X,A,F8.2,A,F8.3)') 'TOTAL HEAT: ',QTOTAL,  |  178
179 |     2                         '   TOTAL RESISTANCE: ',RTOTAL   |  179
180 |          WRITE (6,3)                                            |  180
181 |          DO 90 I=1,N                                            |  181
182 |          IF (MATL(I).EQ.'AIRSPACE'.AND.I.EQ.1) THEN            |  182
183 |             WRITE (6,5) MATL(I),T(I)-273.15,R(I),Q(I),Q(I)     |  183
184 |          ELSE IF (MATL(I).EQ.'AIRSPACE'.AND.I.NE.1) THEN        |  184
185 |             QCONV=(T(I-1)-T(I))/CONV(I)                         |  185
186 |             QRAD=(T(I-1)-T(I))/RAD(I)                           |  186
187 |             WRITE (6,1) MATL(I),T(I)-273.15,R(I),Q(I),QCONV,QRAD|  187
188 |          ELSE                                                   |  188
189 |             WRITE (6,2) MATL(I),T(I)-273.15,R(I),Q(I)           |  189
190 |          END IF                                                 |  190
191 |90        CONTINUE                                               |  191
192 |          WRITE (6,4) 'TEMPERATURES ARE OF COOLER SIDE OF NODE'  |  192
193 |       END IF                                                    |  193
194 |100    CONTINUE                                                  |  194
195 |       GO TO 10                                                  |  195
196 |    END IF                                                       |  196
197 |    STOP                                                         |  197
198 |1   FORMAT (1X,A10,2X,F10.2,3X,F10.3,2X,F10.3,3X,F10.3,3X,F10.3) |  198
199 |2   FORMAT (1X,A10,2X,F10.2,3X,F10.3,2X,F10.3)                   |  199
200 |3   FORMAT ('0MATERIAL     TEMPERATURE  RESISTANCE    HEAT    CONV|  200
201 |   2ECTION    RADIATION',/)                                      |  201
202 |4   FORMAT ('0',A)                                               |  202
203 |5   FORMAT (1X,A10,2X,F10.2,3X,F10.3,2X,F10.3,16X,F10.3)         |  203
204 |6   FORMAT (1X,A7,4(F10.3,A5,:),/,10(8X,4(F10.3,A5,:),/))        |  204
205 |7   FORMAT ('0ITERATION: ',I3,'         INNER LOOP: ',I3)       |  205
206 |8   FORMAT (' ',A10,20(A7,:))                                    |  206
207 |9   FORMAT (' ',F10.3,20(F6.1,1X,:))                             |  207
208 |11  FORMAT ('0',/,20(' ',I6,':     ',A,/)/)                     |  208
209 |12  FORMAT (' ',A10,20('   (',I2,')',:))                        |  209
210 |    END                                                         |  210
```

```
211 |      SUBROUTINE INPUT (THEEND)                                        |    1
212 |C                                                                      |    2
213 |C    @@@@@@                                                           |    3
214 |C    @@@@                                               @             |    4
215 |C    @@@@     @@@@@@    @@@@@@    @@@ @    @@@@@@                      |    5
216 |C    @@@@    @  @@@    @@@  @    @@@  @    @@@@                        |    6
217 |C    @@@@    @  @@@    @@@  @    @@@  @    @@@@                        |    7
218 |C    @@@@    @  @@@    @@@@@@    @@@  @    @@@@                        |    8
219 |C    @@@@@@   @  @@@    @@@       @@@@@@    @@@@                       |    9
220 |C                      @@@                                            |   10
221 |C                                                                     |   11
222 |C    PURPOSE:  INPUTS DATA DESCRIBING THE STOVE / WALL PROTECTION SYSTEM |  12
223 |C             TO BE MODELED                                           |   13
224 |C                                                                     |   14
225 |      INCLUDE 'STOVE.CMN'                                             |   15
226 |      PARAMETER (NVAR=8)                                              |   16
227 |      CHARACTER VAR(NVAR)*6,IN*80,KEYWD*80                            |   17
228 |      INTEGER VLEN(NVAR)                                              |   18
229 |      LOGICAL THEEND,HAVEX,HAVEY                                      |   19
230 |      DATA (VAR(I),VLEN(I),I=1,NVAR) /'XWALL ',5,'YWALL ',5,'TSTOVE',6, | 20
231 |     2 'THICK ',5,'WIDTH ',5,'HEIGHT',6,'K     ',1,'EMMIS ',5/         |  21
232 |C                                                                     |   22
233 |C    LOOK FOR A KEYWORD OR END OF FILE                               |   23
234 |C                                                                     |   24
235 |      THEEND=.TRUE.                                                   |   25
236 |      HAVEX=.FALSE.                                                   |   26
237 |      HAVEY=.FALSE.                                                   |   27
238 |      TITLE='STOVE / WALL PROTECTOR HEAT TRANSFER MODEL'              |   28
239 |      N=0                                                             |   29
240 |      IVAR=0                                                          |   30
241 |      VNAME=' '                                                       |   31
242 |10    READ (5,'(A80)',END=30) IN                                      |   32
243 |      THEEND=.FALSE.                                                  |   33
244 |      IS=INDEX(IN,': ')                                               |   34
245 |      IF (IS.GT.1) THEN                                               |   35
246 |        KEYWD=IN(1:IS-1)                                             |   36
247 |        IF (KEYWD.NE.'END') THEN                                      |   37
248 |C                                                                     |   38
249 |C    XWALL ... X POSITION OF POINT ON THE WALL                       |   39
250 |C                                                                     |   40
251 |          IF (KEYWD.EQ.'XWALL') THEN                                  |   41
252 |            ICHR=IS+2                                                 |   42
253 |            XWALL=FVAL(IN,ICHR)                                       |   43
254 |            HAVEX=.TRUE.                                              |   44
255 |C                                                                     |   45
256 |C    YWALL ... Y POSITION OF POINT ON THE WALL                       |   46
257 |C                                                                     |   47
258 |          ELSE IF (KEYWD.EQ.'YWALL') THEN                             |   48
259 |            ICHR=IS+2                                                 |   49
260 |            YWALL=FVAL(IN,ICHR)                                       |   50
261 |            HAVEY=.TRUE.                                              |   51
262 |C                                                                     |   52
263 |C    AIRSPACE ... AN AIR SPACE BETWEEN TWO SOLID PROTECTORS          |   53
264 |C                                                                     |   54
265 |          ELSE IF (KEYWD.EQ.'AIRSPACE') THEN                          |   55
266 |            N=N+1                                                     |   56
267 |            MATL(N)='AIRSPACE'                                        |   57
268 |            ICHR=IS+2                                                 |   58
269 |            V1=FVAL(IN,ICHR)                                          |   59
270 |            V2=FVAL(IN,ICHR)                                          |   60
271 |            V3=FVAL(IN,ICHR)                                          |   61
272 |            IF (V2.EQ.0..AND.V3.EQ.0.) THEN                           |   62
273 |              T(N)=V1                                                 |   63
274 |              EMMIS(N)=1.0                                            |   64
275 |              HEIGHT(N)=0.                                            |   65
276 |            ELSE                                                      |   66
277 |              L(N)=V1                                                 |   67
278 |              EMMIS(N)=V2                                             |   68
279 |              IF (EMMIS(N).EQ.0.) EMMIS(N)=1.0                        |   69
280 |              T(N)=V3                                                 |   70
```

```
281 |            HEIGHT(N)=HEIGHT(N-1)                              |  71
282 |            WIDTH(N)=WIDTH(N-1)                                |  72
283 |          END IF                                              |  73
284 |C                                                             |  74
285 |C    STOVE ... THE HOT STOVE SURFACE                          |  75
286 |C                                                             |  76
287 |        ELSE IF (KEYWD.EQ.'STOVE') THEN                       |  77
288 |          MATL(0)='STOVE'                                     |  78
289 |          ICHR=IS+2                                           |  79
290 |          EMMIS(0)=FVAL(IN,ICHR)                              |  80
291 |          IF (EMMIS(0).EQ.0.) EMMIS(N)=1.0                    |  81
292 |          HEIGHT(0)=FVAL(IN,ICHR)                             |  82
293 |          WIDTH(0)=FVAL(IN,ICHR)                              |  83
294 |          T(0)=FVAL(IN,ICHR)                                  |  84
295 |C                                                             |  85
296 |C    FOR ... SPECIFIES A SERIES OF CALCULATIONS TO BE DONE    |  86
297 |C                                                             |  87
298 |        ELSE IF (KEYWD.EQ.'FOR') THEN                         |  88
299 |          IVAR=0                                              |  89
300 |          ISUB=0                                              |  90
301 |          DO 20 I=1,NVAR                                      |  91
302 |          J=INDEX(IN,VAR(I)(1:VLEN(I)))                       |  92
303 |          IF (J.NE.0.AND.IN(J-1:J-1).EQ.' ') IVAR=I           |  93
304 |20        CONTINUE                                            |  94
305 |          IR=0                                                |  95
306 |          ICHR=IS+2                                           |  96
307 |          IF (IVAR.EQ.0) THEN                                 |  97
308 |            WRITE (6,1) IN                                    |  98
309 |            GO TO 10                                          |  99
310 |C                                                             | 100
311 |C    IF IT'S A VARIABLE WITH SUBSCRIPT, MAKE SURE ONE'S THERE | 101
312 |C                                                             | 102
313 |          ELSE IF (IVAR.GE.4) THEN                            | 103
314 |            IL=INDEX(IN,'(')                                  | 104
315 |            IR=INDEX(IN,')')                                  | 105
316 |            IF (IL.EQ.0.OR.IR.EQ.0.OR.IL.GT.IR) THEN          | 106
317 |              WRITE (6,2) IN                                  | 107
318 |              GO TO 10                                        | 108
319 |            END IF                                            | 109
320 |            ISUB=FVAL(IN,ICHR)                                | 110
321 |          END IF                                              | 111
322 |          ICHR=IR+1                                           | 112
323 |          VLOWER=FVAL(IN,ICHR)                                | 113
324 |          VUPPER=FVAL(IN,ICHR)                                | 114
325 |          VINCR=FVAL(IN,ICHR)                                 | 115
326 |          IF ((VLOWER.NE.VUPPER.AND.VINCR.EQ.0)               | 116
327 |     2      .OR.(VLOWER.EQ.VUPPER.AND.VINCR.NE.0)             | 117
328 |     3      .OR.(VUPPER.GT.VLOWER.AND.VINCR.LT.0)             | 118
329 |     4      .OR.(VUPPER.LT.VLOWER.AND.VINCR.GT.0)) THEN       | 119
330 |            WRITE (6,4) IN                                    | 120
331 |            GO TO 10                                          | 121
332 |          END IF                                              | 122
333 |          VNAME=VAR(IVAR)                                     | 123
334 |          VNAME(VLEN(IVAR)+1:VLEN(IVAR)+1+IR-IL)=IN(IL:IR)    | 124
335 |C                                                             | 125
336 |C    DEBUG ... TURN DEBUG PRINT ON OR OFF                     | 126
337 |C                                                             | 127
338 |        ELSE IF (KEYWD.EQ.'DEBUG') THEN                       | 128
339 |          IF (INDEX(IN,'OFF').NE.0) DEBUG=.FALSE.             | 129
340 |          IF (INDEX(IN,'ON').NE.0) DEBUG=.TRUE.               | 130
341 |C                                                             | 131
342 |C    PRINTOUT ... SPECIFY LEVEL OF PRINTOUT                   | 132
343 |C                                                             | 133
344 |        ELSE IF (KEYWD.EQ.'PRINTOUT') THEN                    | 134
345 |          IF (INDEX(IN,'FULL').NE.0) FULPRT=.TRUE.            | 135
346 |          IF (INDEX(IN,'FULL').EQ.0) FULPRT=.FALSE.           | 136
347 |C                                                             | 137
348 |C    TITLE ... SPECIFY A TITLE FOR THE PRINTOUT              | 138
349 |C                                                             | 139
350 |        ELSE IF (KEYWD.EQ.'TITLE') THEN                       | 140
```

```
351 |          TITLE=IN(IS+2:80)                                          |  141
352 |C                                                                    |  142
353 |C  IF IT'S NOT ONE OF THE RECOGNIZED KEYWORDS, ASSUME A SOLID PROTECTOR|  143
354 |C                                                                    |  144
355 |        ELSE                                                         |  145
356 |          N=N+1                                                      |  146
357 |          ICHR=IS+2                                                  |  147
358 |          MATL(N)=IN(1:IS-1)                                         |  148
359 |          L(N)=FVAL(IN,ICHR)                                         |  149
360 |          HEIGHT(N)=FVAL(IN,ICHR)                                    |  150
361 |          WIDTH(N)=FVAL(IN,ICHR)                                     |  151
362 |          K(N)=FVAL(IN,ICHR)                                         |  152
363 |          EMMIS(N)=FVAL(IN,ICHR)                                     |  153
364 |          T(N)=FVAL(IN,ICHR)                                         |  154
365 |          IF (L(N).EQ.0..OR.HEIGHT(N).EQ.0..OR.WIDTH(N).EQ.0..OR.    |  155
366 |        2   K(N).EQ.0..OR.EMMIS(N).EQ.0.) THEN                       |  156
367 |            WRITE (6,3) IN                                           |  157
368 |            N=N-1                                                    |  158
369 |            GO TO 10                                                 |  159
370 |          END IF                                                     |  160
371 |        END IF                                                       |  161
372 |        GO TO 10                                                     |  162
373 |      END IF                                                         |  163
374 |    END IF                                                           |  164
375 |C                                                                    |  165
376 |C  DATA HAS BEEN READ IN, CHECK CONSISTENCY OF DATA INPUT            |  166
377 |C                                                                    |  167
378 |30  IF (THEEND) THEN                                                 |  168
379 |      RETURN                                                         |  169
380 |    ELSE IF (N.LE.1) THEN                                            |  170
381 |      WRITE (6,*) 'DATA INPUT ERROR, TOO FEW NODES SPECIFIED.'       |  171
382 |    ELSE                                                             |  172
383 |      IF (DEBUG.AND.IVAR.NE.0) THEN                                  |  173
384 |        IF (IVAR.LT.4) THEN                                          |  174
385 |          WRITE (6,5) VAR(IVAR),VLOWER,VUPPER,VINCR                  |  175
386 |        ELSE                                                         |  176
387 |          WRITE (6,6) VAR(IVAR),ISUB,VLOWER,VUPPER,VINCR             |  177
388 |        END IF                                                       |  178
389 |      END IF                                                         |  179
390 |      DO 40 I=1,N                                                    |  180
391 |      IF (DEBUG) CALL PSUM(I)                                        |  181
392 |      IF (MATL(I).EQ.'AIRSPACE') THEN                                |  182
393 |        IF ((L(I).LE.0..AND.I.NE.N).OR.(HEIGHT(I).LE.0..AND.I.NE.N)  |  183
394 |      2 .OR.(HEIGHT(I).NE.0..AND.I.EQ.N).OR.EMMIS(I).LE.0.) THEN     |  184
395 |          WRITE (6,'(1X,A,I3)') 'INCORRECTLY SPECIFIED AIR SPACE.',I |  185
396 |          STOP 'INPUT DATA ERRORS, AIR SPACE'                        |  186
397 |        END IF                                                       |  187
398 |      ELSE                                                           |  188
399 |        IF (L(I).LE.0..OR.HEIGHT(I).LE.0..OR.WIDTH(I).LE.0..OR.      |  189
400 |      2   K(I).LE.0..OR.EMMIS(I).LE.0.) THEN                         |  190
401 |          WRITE (6,'(1X,A,I3)') 'INCORRECTLY SPECIFIED PROTECTOR.',I |  191
402 |          STOP 'INPUT DATA ERRORS, SOLID PROTECTOR'                  |  192
403 |        END IF                                                       |  193
404 |      END IF                                                         |  194
405 |40    CONTINUE                                                       |  195
406 |      IF (XWALL.LT.0..OR.YWALL.LT.0.) THEN                           |  196
407 |        WRITE (6,*) 'INCORRECTLY SPECIFIED POINT ON WALL.'           |  197
408 |        STOP 'DATA INPUT ERRORS, XWALL & YWALL'                      |  198
409 |      END IF                                                         |  199
410 |      IF (T(0).LE.T(N)) THEN                                         |  200
411 |        WRITE (6,*) 'INCORRECTLY SPECIFIED ENDPOINT TEMPERATURES.'   |  201
412 |        STOP 'DATA INPUT ERRORS, T(0) & T(N)'                        |  202
413 |      END IF                                                         |  203
414 |      IF (T(0).LE.0..OR.WIDTH(0).LE.0..OR.HEIGHT(0).LE.0..OR.EMMIS(0)|  204
415 |      2 .LE.0.) THEN                                                 |  205
416 |        WRITE (6,*) 'INCORRECTLY SPECIFIED STOVE PARAMETERS.'        |  206
417 |        STOP 'DATA INPUT ERRORS, STOVE'                              |  207
418 |      END IF                                                         |  208
419 |    END IF                                                           |  209
420 |    IF (MATL(N).EQ.'AIRSPACE') HEIGHT(N)=HEIGHT(N-1)                 |  210
```

```
421 |       ZSTOVE=L(1)                                                        211
422 |       HSTOVE=HEIGHT(0)                                                   212
423 |       WSTOVE=WIDTH(0)                                                    213
424 |C                                                                         214
425 |C   IF NOT POSITION HAS BEEN SPECIFIED, USE MIDPOINT OF STOVE            215
426 |C                                                                         216
427 |       IF (.NOT. HAVEX) THEN                                             217
428 |          XWALL=WSTOVE/2.                                                218
429 |       END IF                                                            219
430 |       IF (.NOT. HAVEY) THEN                                             220
431 |          YWALL=HSTOVE/2.                                                221
432 |       END IF                                                            222
433 |C                                                                         223
434 |C   IF NO INCREMENT HAS BEEN SPECIFIED, MAKE ONE UP                      224
435 |C                                                                         225
436 |       IF (IVAR.EQ.0) THEN                                               226
437 |          IVAR=1                                                         227
438 |          VLOWER=XWALL                                                   228
439 |          VUPPER=XWALL                                                   229
440 |          VINCR=1.0                                                      230
441 |       END IF                                                            231
442 |C                                                                         232
443 |C   PRINT OUT A DESCRIPTION OF THE STOVE / WALL SYSTEM AS SPECIFIED      233
444 |C                                                                         234
445 |       WRITE (6,11) TITLE,N+1,XWALL,YWALL                               235
446 |       IF (IVAR.GT.0.AND.IVAR.LT.4) THEN                                236
447 |          WRITE (6,5) VAR(IVAR),VLOWER,VUPPER,VINCR                      237
448 |       ELSE IF (IVAR.GT.4) THEN                                         238
449 |          WRITE (6,6) VAR(IVAR),ISUB,VLOWER,VUPPER,VINCR                 239
450 |       END IF                                                            240
451 |       WRITE (6,12)                                                      241
452 |       DO 50 I=0,N                                                       242
453 |       IF (I.EQ.0.OR.I.EQ.N) THEN                                        243
454 |          IF (MATL(I).EQ.'STOVE') THEN                                  244
455 |             WRITE (6,13) I,MATL(I),HEIGHT(I),WIDTH(I),EMMIS(I),T(I)-273.15  245
456 |          ELSE IF (MATL(I).EQ.'AIRSPACE') THEN                          246
457 |             WRITE (6,14) I,MATL(I),L(I),EMMIS(I),T(I)-273.15           247
458 |          ELSE                                                          248
459 |             WRITE (6,15) I,MATL(I),HEIGHT(I),WIDTH(I),L(I),EMMIS(I),K(I),  249
460 |     2       T(I)-273.15                                                 250
461 |          END IF                                                        251
462 |       ELSE                                                             252
463 |          IF (MATL(I).EQ.'STOVE') THEN                                  253
464 |             WRITE (6,13) I,MATL(I),HEIGHT(I),WIDTH(I),EMMIS(I)         254
465 |          ELSE IF (MATL(I).EQ.'AIRSPACE') THEN                          255
466 |             WRITE (6,14) I,MATL(I),L(I),EMMIS(I)                       256
467 |          ELSE                                                          257
468 |             WRITE (6,15) I,MATL(I),HEIGHT(I),WIDTH(I),L(I),EMMIS(I),K(I)  258
469 |          END IF                                                        259
470 |       END IF                                                           260
471 |50     CONTINUE                                                          261
472 |       RETURN                                                            262
473 |C                                                                         263
474 |1      FORMAT ('0SYNTAX ERROR ON ''FOR'' STATEMENT, ILLEGAL OR NO VARIABL  264
475 |     2E SPECIFIED.',/,' ',A79,//)                                        265
476 |2      FORMAT ('0SYNTAX ERROR ON ''FOR'' STATEMENT, SUBSCRIPT REQUIRED FO  266
477 |     2R VARIABLE SPECIFIED.',/,' ',A79,//)                               267
478 |3      FORMAT ('0SYNTAX ERROR ON STATEMENT, UNRECOGNIZED KEYWORD.',/,    268
479 |     2 ' ',A79,//)                                                       269
480 |4      FORMAT ('0SYNTAX ERROR ON ''FOR'' STATEMENT, RANGE AND INCREMENT I  270
481 |     2NCONSISTENT.',/,' ',A79,//)                                        271
482 |5      FORMAT ('0SERIES OF CALCULATIONS FOR VARIABLE ',A,': ',3F10.3)    272
483 |6      FORMAT ('0SERIES OF CALCULATIONS FOR VARIABLE ',A,'(',I2,         273
484 |     2 '): ',3F10.3)                                                     274
485 |11     FORMAT ('1',A,//,                                                 275
486 |     2 ' NUMBER OF NODES IN CALCULATION: ',I2,/,' POINT ON WALL:  (X):'  276
487 |     3 F10.3,T41,'(Y):',F10.3)                                           277
488 |12     FORMAT ('0I   MATERIAL            HEIGHT   WIDTH    THICK   EMISS  278
489 |     2      K     TEMPERATURE',/,                                        279
490 |     3          '                         (m)      (m)      (m)          280
```

```
491 |     4   (W/m K)      (°C)',/,' ',78('—'),/)                            281
492 |13   FORMAT (1X,I2,2X,A,T26,1X,F6.2,T35,F6.2,T51,F6.2,T70,F7.2)        282
493 |14   FORMAT (1X,I2,2X,A,T43,F6.2,T51,F6.2,T70,F7.2)                    283
494 |15   FORMAT (1X,I2,2X,A,T26,1X,4(F6.2,2X),F8.3,2X,F8.2)                284
495 |     END                                                              285
```

```
496 |       DOUBLE PRECISION FUNCTION FVAL (IN,ICHR)                    1
497 |C                                                                  2
498 |C    @@@@@@@@                         @@@                          3
499 |C    @@@@                             @@@                          4
500 |C    @@@@        @@@  @    @@@@@@      @@@                          5
501 |C    @@@@@@@@    @@@  @        @       @@@                          6
502 |C    @@@@        @@@  @    @@@@@@       @@@                         7
503 |C    @@@@         @@@@     @ @@@        @@@                         8
504 |C    @@@@          @@     @@@@@@@       @@@                         9
505 |C                                                                 10
506 |C ARGUMENTS:   IN:     STRING CONTAINING (MAYBE) NUMBER           11
507 |C              ICHR:   (INPUT) BEGINNING CHARACTER POSITION        12
508 |C                      (OUTPUT) NEXT CHARACTER POSITION            13
509 |C                                                                 14
510 |C PURPOSE:  DECODE NEXT NUMBER IN STRING AS A DOUBLE PRECISION VALUE  15
511 |C                                                                 16
512 |      IMPLICIT DOUBLE PRECISION (A-H,O-Z)                         17
513 |      CHARACTER IN*(*),FORMAT*10                                  18
514 |      IL=LEN(IN)                                                  19
515 |      IFIRST=ICHR                                                 20
516 |      DO 20 I=IFIRST,IL                                           21
517 |      IF ((IN(I:I).GE.'0'.AND.IN(I:I).LE.'9').OR.IN(I:I).EQ.'.'   22
518 |     2 .OR.IN(I:I).EQ.'+'.OR.IN(I:I).EQ.'-' ) THEN                23
519 |C                                                                 24
520 |C   THERE IS A NUMBER ON THE CARD, FIND OUT WHAT IT IS            25
521 |C                                                                 26
522 |         DO 10 J=I,IL                                             27
523 |C                                                                 28
524 |C   IF WE FIND THE END OF THE NUMBER, READ IT FROM THE LINE       29
525 |C                                                                 30
526 |         IF ((IN(J:J).LT.'0'.OR.IN(J:J).GT.'9').AND.IN(J:J).NE.'.'  31
527 |     2 .AND.IN(J:J).NE.'+'.AND.IN(J:J).NE.'-' ) THEN              32
528 |            WRITE (FORMAT,30) J-I                                 33
529 |            READ (IN(I:J-1),FORMAT) VAL                           34
530 |            FVAL=VAL                                              35
531 |            ICHR=J                                                36
532 |            RETURN                                                37
533 |         END IF                                                   38
534 |10       CONTINUE                                                 39
535 |C                                                                 40
536 |C   IF WE GET TO THE END OF THE LINE WITHOUT FINDING END OF NUMBER,  41
537 |C   JUST READ THE NUMBER                                          42
538 |C                                                                 43
539 |         WRITE (FORMAT,30) IL-I+1                                 44
540 |         READ (IN(I:IL),FORMAT) VAL                               45
541 |         FVAL=VAL                                                 46
542 |         ICHR=J                                                   47
543 |         RETURN                                                   48
544 |      END IF                                                      49
545 |20    CONTINUE                                                    50
546 |C                                                                 51
547 |C   IF NO NUMBER IS ON THE CARD, JUST RETURN A 0.                 52
548 |C                                                                 53
549 |      FVAL=0.                                                     54
550 |      RETURN                                                      55
551 |C                                                                 56
552 |30    FORMAT ('(F',I2.2,'.0)')                                    57
553 |      END                                                         58
```

```
554 |       SUBROUTINE HEATS                                                  |        1
555 |C                                                                        |        2
556 |C     @@@@    @                                                          |        3
557 |C     @@@@    @                             @                            |        4
558 |C     @@@@    @   @@@@@@    @@@@@@    @@@@@@    @@@@@@                     |        5
559 |C     @@@@@@@@   @  @@@       @      @@@@     @@@                         |        6
560 |C     @@@@    @   @@@@@@    @@@@@@    @@@@    @@@@@@                       |        7
561 |C     @@@@    @   @         @  @@@    @@@@       @@@                      |        8
562 |C     @@@@    @   @@@@@@    @@@@@@    @@@@    @@@@@@                       |        9
563 |C                                                                        |       10
564 |C  ARGUMENTS:   NONE                                                     |       11
565 |C                                                                        |       12
566 |C  PURPOSE:   CALCULATES TOTAL HEAT AND TOTAL RESISTANCE THROUGH WALL    |       13
567 |C             PROTECTORS                                                 |       14
568 |C                                                                        |       15
569 |       INCLUDE 'STOVE.CMN'                                               |       16
570 |C                                                                        |       17
571 |C  JUST SUM UP RESISTANCES TO MAKE UP TOTAL RESISTANCE                   |       18
572 |C                                                                        |       19
573 |       RTOTAL=0.                                                         |       20
574 |       DO 10 I=1,N                                                       |       21
575 |       CALL HEAT(I)                                                      |       22
576 |10     RTOTAL=RTOTAL+R(I)                                                |       23
577 |C                                                                        |       24
578 |C  TOTAL HEAT IS JUST DELTA T / TOTAL RESISTANCE                         |       25
579 |C                                                                        |       26
580 |       QTOTAL=(T(0)-T(N))/RTOTAL                                         |       27
581 |       RETURN                                                            |       28
582 |       END                                                              |       29
```

```
583 |       SUBROUTINE HEAT(I)                                                   1
584 |C                                                                           2
585 |C    @@@@    @                                                              3
586 |C    @@@@    @                                        @                     4
587 |C    @@@@    @    @@@@@@    @@@@@@    @@@@@@                                 5
588 |C    @@@@@@@@    @ @@@          @    @@@@                                    6
589 |C    @@@@    @    @@@@@@    @@@@@@    @@@@                                   7
590 |C    @@@@    @    @         @ @@@    @@@@                                   8
591 |C    @@@@    @    @@@@@@    @@@@@@    @@@@                                   9
592 |C                                                                          10
593 |C    ARGUMENTS:    I:   ELEMENT NUMBER                                     11
594 |C                                                                          12
595 |C    PURPOSE:   CALCULATES HEAT THROUGH ELEMENT NUMBER I                   13
596 |C                                                                          14
597 |       INCLUDE 'STOVE.CMN'                                                 15
598 |       DATA SIGMA / 5.67D-8 /                                              16
599 |       IF (MATL(I).NE.'AIRSPACE') THEN                                     17
600 |C                                                                          18
601 |C    MATERIAL IS A SOLID, CONDUCTION ONLY                                  19
602 |C                                                                          20
603 |          R(I)=L(I)/K(I)                                                   21
604 |       ELSE IF (MATL(I).EQ.'AIRSPACE'.AND.I.EQ.1) THEN                     22
605 |C                                                                          23
606 |C    MATERIAL IS AND AIRSPACE NEXT TO STOVE, CALCULATE FOR POINT ON WALL   24
607 |C                                                                          25
608 |          XNOTS=XWALL-(XSTOVE-WSTOVE*.5)                                   26
609 |          YNOTS=YWALL-YSTOVE                                               27
610 |          ZNOTS=ZSTOVE                                                     28
611 |          CF(I)=CFIGS(XNOTS,YNOTS,ZNOTS)-CFIGS(XNOTS-WSTOVE,YNOTS,ZNOTS)   29
612 |     2         +CFIGS(XNOTS-WSTOVE,YNOTS-HSTOVE,ZNOTS)                     30
613 |     3         -CFIGS(XNOTS,YNOTS-HSTOVE,ZNOTS)                            31
614 |          RAD(I)=1./(CF(I)*SIGMA*EMMIS(I)*(T(I-1)**2+T(I)**2)              32
615 |     2           *(T(I-1)+T(I)))                                           33
616 |          RMTEMP=293.15                                                    34
617 |          RLOSS=(T(I-1)-T(I))/((T(I)**4-RMTEMP**4)*SIGMA*EMMIS(I)          35
618 |     2           *(1-CF(I)))                                               36
619 |          R(I)=1./(1./RAD(I)-1./RLOSS)                                     37
620 |       ELSE IF (MATL(I).EQ.'AIRSPACE'.AND.I.NE.N) THEN                     38
621 |C                                                                          39
622 |C    MATERIAL IS AN AIRSPACE, BUT NOT NEXT TO STOVE                        40
623 |C                                                                          41
624 |          CF(I)=CFIGP(HEIGHT(I),WIDTH(I),L(I))                            42
625 |          H(I)=HCONV(T(I-1),T(I),HEIGHT(I))                               43
626 |          CONV(I)=1./H(I)                                                  44
627 |          RAD(I)=1./(CF(I)*SIGMA*EMMIS(I)*(T(I-1)**2+T(I)**2)              45
628 |     2            *(T(I-1)+T(I)))                                          46
629 |          R(I)=1./(1./CONV(I)+1./RAD(I))                                   47
630 |       ELSE                                                                48
631 |C                                                                          49
632 |C    MATERIAL IS AN AIRSPACE AND LAST ELEMENT ... THE GREAT OUTDOORS       50
633 |C                                                                          51
634 |          CF(I)=1.                                                         52
635 |          H(I)=HCONV(T(I-1),T(I),HEIGHT(I))                               53
636 |          CONV(I)=1./H(I)                                                  54
637 |          RAD(I)=1./(CF(I)*SIGMA*EMMIS(I)*(T(I-1)**2+T(I)**2)              55
638 |     2            *(T(I-1)+T(I)))                                          56
639 |          R(I)=1./(1./CONV(I)+1./RAD(I))                                   57
640 |       END IF                                                              58
641 |       Q(I)=(T(I-1)-T(I))/R(I)                                             59
642 |       RETURN                                                              60
643 |       END                                                                 61
```

```
644 |      DOUBLE PRECISION FUNCTION CFIGS (A,B,C)                          |    1
645 |C                                                                      |    2
646 |C    @@@@@@@@   @@@@    @@@@                                           |    3
647 |C    @   @@@@   @                        @                            |    4
648 |C    @   @@@@ @@@@@@   @@@@   @@@@@@  @@@@@@                           |    5
649 |C    @        @@@@    @@@@   @@@@@@  @@@                               |    6
650 |C    @   @@@@  @@@@    @@@@    @     @@@@@@                            |    7
651 |C    @   @@@@  @@@@    @@@@  @@@@@@@@   @@@                            |    8
652 |C    @@@@@@@@  @@@@    @@@@   @  @@@@  @@@@@@                          |    9
653 |C                            @@@@@@@@                                 |   10
654 |C                                                                     |   11
655 |C  ARGUMENTS:   A:  WIDTH OF RECTANGLE                                |   12
656 |C              B:  HEIGHT OF RECTANGLE                                |   13
657 |C              C:  DISTANCE TO POINT OF CALCULATION                   |   14
658 |C                                                                     |   15
659 |C  PURPOSE:  CALCULATES RADIATION CONFIGURATION FACTOR FOR A PLANE    |   16
660 |C            ELEMENT TO A PLANE PARALLEL RECTANGLE.                   |   17
661 |C                                                                     |   18
662 |C  SOURCE:  THERMAL RADIATION HEAT TRANSFER, SEIGEL & HOWELL.        |   19
663 |C                                                                     |   20
664 |    IMPLICIT DOUBLE PRECISION (A-H,O-Z)                               |   21
665 |    PI=3.14159                                                        |   22
666 |    X=A/C                                                             |   23
667 |    Y=B/C                                                             |   24
668 |    CFIGS=1./(2*PI)*(X/SQRT(1+X**2)*ATAN(Y/SQRT(1+X**2))             |   25
669 |   2 + Y/SQRT(1+Y**2)*ATAN(X/SQRT(1+Y**2)))                          |   26
670 |    RETURN                                                            |   27
671 |    END                                                              |   28
```

```
672 |        DOUBLE PRECISION FUNCTION CFIGP (A,B,C)                    |        1
673 |C                                                                 |        2
674 |C     @@@@@@@@    @@@@    @@@@                                     |        3
675 |C     @   @@@@    @                               @               |        4
676 |C     @    @@@@   @@@@@@   @@@@    @@@@@@    @@@@@@                 |        5
677 |C     @           @@@@    @@@@    @@@@@@   @@@  @                  |        6
678 |C     @   @@@@    @@@@    @@@@      @       @@@  @                 |        7
679 |C     @    @@@@   @@@@    @@@@    @@@@@@@   @@@@@@                  |        8
680 |C     @@@@@@@@    @@@@    @@@@    @   @@@@   @@@                    |        9
681 |C                                @@@@@@@@   @@@                    |       10
682 |C                                                                 |       11
683 |C  ARGUMENTS:    A:  WIDTH OF RECTANGLE                           |       12
684 |C               B:  HEIGHT OF RECTANGLE                           |       13
685 |C               C:  DISTANCE BETWEEN RECTANGLES                   |       14
686 |C                                                                 |       15
687 |C  PURPOSE:  CALCULATES RADIATION CONFIGURATION FACTOR FOR TWO    |       16
688 |C            IDENTICAL, PARALLEL, DIRECTLY OPPOSED RECTANGLES.    |       17
689 |C                                                                 |       18
690 |C  SOURCE:  THERMAL RADIATION HEAT TRANSFER, SEIGEL & HOWELL.    |       19
691 |C                                                                 |       20
692 |      IMPLICIT DOUBLE PRECISION (A-H,O-Z)                         |       21
693 |      PI=3.14159                                                  |       22
694 |      X=A/C                                                       |       23
695 |      Y=B/C                                                       |       24
696 |      CFIGP=2./(PI*X*Y)*(LOG(((1+X*X)*(1+Y*Y))/(1+X*X+Y*Y))**0.5 +|       25
697 |     2 X*SQRT(1+Y*Y)*ATAN(X/SQRT(1+Y*Y)) +                        |       26
698 |     3 Y*SQRT(1+X*X)*ATAN(Y/SQRT(1+X*X)) -                        |       27
699 |     4 X*ATAN(X) - Y*ATAN(Y))                                     |       28
700 |      RETURN                                                      |       29
701 |      END                                                        |       30
```

```
702 |        DOUBLE PRECISION FUNCTION HCONV(T1,T2,L)                        |    1
703 |C                                                                       |    2
704 |C    @@@@    @                                                          |    3
705 |C    @@@@    @                                                          |    4
706 |C    @@@@    @   @@@@@@    @@@@@@    @@@@@@   @@@  @                      |    5
707 |C    @@@@@@@@  @  @@@    @@@  @   @  @@@   @@@  @                         |    6
708 |C    @@@@    @  @         @@@  @    @  @@@   @@@  @                       |    7
709 |C    @@@@    @  @  @@@    @@@  @    @  @@@    @@@@                        |    8
710 |C    @@@@    @  @@@@@@    @@@@@@    @  @@@     @@                         |    9
711 |C                                                                       |   10
712 |C  ARGUMENTS:    T1:   TEMPERATURE OF HOTTER SURFACE                     |   11
713 |C                T2:   TEMPERATURE OF COOLER SURFACE                     |   12
714 |C                L:    HEIGHT OF SURFACES                                |   13
715 |C                                                                       |   14
716 |C  PURPOSE:  CALCULATES FREE CONVECTION HEAT TRANSFER COEFFICIENT FOR    |   15
717 |C            A VERTICAL SURFACE.                                         |   16
718 |C                                                                       |   17
719 |C  SOURCE:   FUNDAMENTALS OF HEAT TRANSFER, INCORPERA & DEWITT.          |   18
720 |C                                                                       |   19
721 |      IMPLICIT DOUBLE PRECISION (A-H,O-Z)                               |   20
722 |      DOUBLE PRECISION K,NU,L,NUSELT                                    |   21
723 |      DIMENSION C(3,5)                                                  |   22
724 |      DATA ((C(I,J),J=1,5),I=1,3) /                                     |   23
725 |     2 -.381021E-2,   .132063E-3, -.117332E-6,   .687499E-10, -.127680E-13|  24
726 |     3,-.167333E-4,   .143076E-6, -.249135E-10, .781850E-13, -.127693E-16|  25
727 |     4,-.501195E-5,   .468550E-7,  .881329E-10,-.117315E-13,  .307192E-17|  26
728 |     5 /                                                                |   27
729 |      TF=(T1+T2)/2                                                      |   28
730 |      DELTAT=(T1-T2)                                                    |   29
731 |      K=C(1,1)+C(1,2)*TF+C(1,3)*TF*TF+C(1,4)*TF**3+C(1,5)*TF**4          |   30
732 |      ALPHA=C(2,1)+C(2,2)*TF+C(2,3)*TF*TF+C(2,4)*TF**3+C(2,5)*TF**4      |   31
733 |      NU=C(3,1)+C(3,2)*TF+C(3,3)*TF*TF+C(3,4)*TF**3+C(3,5)*TF**4         |   32
734 |      PR=NU/ALPHA                                                       |   33
735 |      RA=9.8*(1./TF)*ABS(DELTAT)*L**3/(NU*ALPHA)                         |   34
736 |      NUSELT=(0.825+0.387*RA**(1./6.)/(1.+(0.492/PR)**(9./16.))          |   35
737 |     2 **(8./27.))**2                                                   |   36
738 |      HCONV=NUSELT*K/L                                                  |   37
739 |      RETURN                                                            |   38
740 |      END                                                              |   39
```

```
741 |        CHARACTER*5 FUNCTION CMET(VALUE,EPS)                    |    1
742 |C                                                              |    2
743 |C    @@@@@@@@                                                  |    3
744 |C    @   @@@@                               @                  |    4
745 |C    @   @@@@  @@@@@@    @@@@@    @@@@@                         |    5
746 |C    @         @ @ @@@   @ @@@    @@@@                          |    6
747 |C    @   @@@@  @ @ @@@   @@@@@@   @@@@                          |    7
748 |C    @   @@@@  @ @ @@@   @        @@@@                          |    8
749 |C    @@@@@@@@  @ @ @@@   @@@@@@   @@@@                          |    9
750 |C                                                              |   10
751 |C  ARGUMENTS:  VALUE:  NUMBER TO BE EVALUATED                  |   11
752 |C             EPS:    ACCEPTANCE CRITERION FOR VALUE           |   12
753 |C                                                              |   13
754 |C  PURPOSE:  FUNCTIONS RETURNS A CHARACTER INDICATION OF WHETHER THE |   14
755 |C            VALUE IS WITHIN LIMITS.  USED FOR DEBUG PRINTOUT  |   15
756 |C                                                              |   16
757 |      IMPLICIT DOUBLE PRECISION (A-H,O-Z)                      |   17
758 |      IF (ABS(VALUE).LE.EPS) THEN                              |   18
759 |        CMET='(IN) '                                          |   19
760 |      ELSE                                                     |   20
761 |        CMET='(OUT)'                                          |   21
762 |      END IF                                                   |   22
763 |      RETURN                                                   |   23
764 |      END                                                      |   24
```

```
765 |        SUBROUTINE PSUM(I)                                                    1
766 |C                                                                             2
767 |C       @@@@@@@@                                                              3
768 |C       @@@@    @                                                             4
769 |C       @@@@    @   @@@@@@    @@@  @    @@@@@@@                                5
770 |C       @@@@@@@@   @@@        @@@  @    @ @ @@@                                6
771 |C       @@@@        @@@@@@    @@@  @    @ @ @@@                                7
772 |C       @@@@           @@@    @@@  @    @ @ @@@                                8
773 |C       @@@@        @@@@@@    @@@@@@    @ @ @@@                                9
774 |C                                                                            10
775 |C   ARGUMENTS:  I:  SURFACE NUMBER FOR SUMMARY PRINTOUT                       11
776 |C                                                                            12
777 |C   PURPOSE:  PRINTS OUT ALL THE VARIABLES IN THE COMMON BLOCK.  USED        13
778 |C             FOR DEBUG PRINTOUT.                                            14
779 |C                                                                            15
780 |       INCLUDE 'STOVE.CMN'                                                   16
781 |       WRITE (6,10) I,MATL(I),T(I),R(I),L(I),K(I),H(I),CF(I),EMMIS(I),       17
782 |      2 Q(I),CONV(I),RAD(I),HEIGHT(I),WIDTH(I),XSTOVE,YSTOVE,ZSTOVE,         18
783 |      3 WSTOVE,HSTOVE,XWALL,YWALL,RTOTAL,QTOTAL,N                            19
784 |       RETURN                                                                20
785 |C                                                                            21
786 |10     FORMAT ('0CURRENT VALUES FOR SPACE ',I2,'    MATERIAL IS ',A,/,       22
787 |      2 ' TEMPERATURE:',F10.3,T41,'RESISTANCE:',F10.3,/,                     23
788 |      3 ' THICKNESS:',F10.3,T41,'THERMAL CONDUCTIVITY:',E12.5,/,             24
789 |      4 ' H:',F10.3,T41,'CONFIGURATION FACTOR:',F10.3,/,                     25
790 |      5 ' EMISSIVITY:',F10.3,T41,'INDIVIDUAL HEAT:',F10.3,/,                 26
791 |      6 ' CONV. RESISTANCE:',F10.3,T41,'RAD. RESISTANCE:',F10.3,/,           27
792 |      7 ' HEIGHT:',F10.3,T41,'WIDTH:',F10.3,/,                               28
793 |      8 ' XSTOVE:',F10.3,T31,'YSTOVE:',F10.3,T61,'ZSTOVE:',F10.3,/,          29
794 |      9 ' WSTOVE:',F10.3,T31,'HSTOVE:',F10.3,/,                              30
795 |      * ' XWALL: ',F10.3,T31,'YWALL: ',F10.3,/,                              31
796 |      1 ' RTOTAL:',F10.3,T31,'QTOTAL:',F10.3,T61,'N:      ',I10)             32
797 |       END                                                                   33
```

```
798 |        CHARACTER*60 FUNCTION PMATL(MATL1,MATL2)              |    1
799 |C                                                            |    2
800 |C    @@@@@@@@                                     @@@        |    3
801 |C    @@@@    @                          @         @@@        |    4
802 |C    @@@@    @   @@@@@@@    @@@@@@    @@@@@@    @@@            |    5
803 |C    @@@@@@@@@  @ @ @@@         @     @@@@      @@@            |    6
804 |C    @@@@       @ @ @@@    @@@@@@@    @@@@      @@@            |    7
805 |C    @@@@       @ @ @@@    @   @@@    @@@@      @@@            |    8
806 |C    @@@@       @ @ @@@    @@@@@@@    @@@@      @@@            |    9
807 |C                                                            |   10
808 |C                                                            |   11
809 |C  ARGUMENTS:  MATL1:  DESCRIPTION OF MATERIAL CLOSER TO APPLIANCE  |   12
810 |C             MATL2:  DESCRIPTION OF MATERIAL FURTHER AWAY FROM APPLIA|NCE  13
811 |C                                                            |   14
812 |C  PURPOSE:  CREATES A CONCATENATED DESCRIPTION OF TWO MATERIALS FOR  |   15
813 |C            PRINTOUT                                        |   16
814 |C                                                            |   17
815 |      CHARACTER*40 MATL1,MATL2                               |   18
816 |      PMATL=MATL1                                            |   19
817 |      DO 10 I=40,1,-1                                        |   20
818 |      IF (MATL1(I:I).NE.' ') THEN                            |   21
819 |        PMATL(I+1:I+3)=' / '                                 |   22
820 |        GO TO 20                                             |   23
821 |      END IF                                                 |   24
822 |10    CONTINUE                                               |   25
823 |      PMATL=' '                                              |   26
824 |20    DO 30 I=40,1,-1                                        |   27
825 |      IF (PMATL(I:I).NE.' ') THEN                            |   28
826 |        PMATL(I+2:60)=MATL2                                  |   29
827 |        RETURN                                               |   30
828 |      END IF                                                 |   31
829 |30    CONTINUE                                               |   32
830 |      PMATL=MATL2                                            |   33
831 |      RETURN                                                 |   34
832 |      END                                                    |   35
```

```
     |C      COMMON BLOCK FOR PROGRAM STOVE
     |C
  1  |       IMPLICIT DOUBLE PRECISION (A-H,O-Z)                              |          1
  2  |C                                                                       |          2
  3  |       PARAMETER (MAXPRO=20)                                            |          3
  4  |C                                                                       |          4
  5  |       DOUBLE PRECISION L,K                                             |          5
  6  |       CHARACTER MATL*40,VNAME*10,TITLE*80                              |          6
  7  |       LOGICAL DEBUG,FULPRT                                             |          7
  8  |       COMMON /NSTOVE/ T(0:MAXPRO),R(0:MAXPRO),L(0:MAXPRO),K(0:MAXPRO), |          8
  9  |      2 H(0:MAXPRO),CF(0:MAXPRO),EMMIS(0:MAXPRO),Q(0:MAXPRO),           |          9
 10  |      3 CONV(0:MAXPRO),RAD(0:MAXPRO),HEIGHT(0:MAXPRO),WIDTH(0:MAXPRO),  |         10
 11  |      4 XSTOVE,YSTOVE,ZSTOVE,WSTOVE,HSTOVE,XWALL,YWALL,RTOTAL,QTOTAL,N, |         11
 12  |      5 IVAR,ISUB,VLOWER,VUPPER,VINCR,DEBUG,FULPRT                      |         12
 13  |       COMMON /CSTOVE/ MATL(0:MAXPRO),VNAME,TITLE                       |         13
 14  |C                                                                       |         14
```

**Appendix B:    Data Input for STOVE**

The data input for stove takes the form of six different key words with arguments to specify values which depend upon the key word.  In most cases, the order of the key words is unimportant, except as noted below.  A description of each of the input key words and values which go on the same line are presented below:


| | |
|---|---|
| **STOVE** | &lt;height&gt; &lt;width&gt; &lt;emissivity&gt; &lt;temperature&gt; |
| **AIRSPACE** | &lt;thickness&gt; &lt;emissivity&gt; |
| **FOR** | &lt;variable&gt; = &lt;lower&gt; &lt;upper&gt; &lt;increment&gt; |
| **XWALL** | &lt;x position&gt; |
| **YWALL** | &lt;y position&gt; |
| **PROTECTOR** | &lt;thickness&gt; &lt;height&gt; &lt;width&gt; &lt;k&gt; &lt;emissivity&gt; &lt;temperature&gt; |


**BOLDFACE** type are required key words. Words in &lt;brackets&gt; specify numeric inputs as follows:


&lt;emissivity&gt;    specifies the emissivity of the cooler surface of the material.  If specified for an airspace, it is the emissivity of the surface adjacent to the airspace at the farther distance from the stove.


&lt;height&gt;    specifies the height of the stove or protector in meters.


&lt;increment&gt;    specifies the amount to increment the variable &lt;variable&gt; in the **FOR** statement for each calculation to be performed.  The first calculation is done with &lt;variable&gt; equal to the value &lt;lower&gt;; the second calculation is done with &lt;variable&gt; equal to the value &lt;lower&gt; + &lt;increment&gt; and so forth until the value of &lt;variable&gt; is greater than or equal to the value of

<upper>.  The units for the number are the same as those for the variable <variable>.

<k>                  specifies the thermal conductivity of the solid protector in W/m·K.

<lower>              specifies the beginning value of the variable <variable> in the **FOR** statement for each calculation to be performed.  The first calculation is done with <variable> equal to the value <lower>; the second calculation is done with <variable> equal to the value <lower> + <increment> and so forth until the value of <variable> is greater than or equal to the value of <upper>.  The units for the number are the same as those for the variable <variable>.

<temperature>        specifies the temperature of the stove surface, protector, or airspace in K.  Temperatures are only specified for the stove surface (surface number 0) and for the outermost surface or airspace (surface number N).

<thickness>          specifies the thickness of the material (for a protector) or the distance between surfaces (for an airspace).

<variable>           specifies the variable to be incremented in each calculation to be done.  The first calculation is done with <variable> equal to the value <lower>; the second calculation is done

with <variable> equal to the value <lower> + <increment> and
so forth until the value of <variable> is greater than or
equal to the value of <upper>.  Legal variables which may be
used are:  T(0) -- the stove temperature, width(i), k(i),
xwall, ywall, emissivity(i), height(i), l(i).

<width>          specifies the width of the stove or protector in meters.

<x position>     specifies the x position of the point on the wall at which the
                 calculation is to done in meters.

<y position>     specifies the y position of the point on the wall at which the
                 calculation is to done in meters.

NBS-114A (REV. 2-80)

| U.S. DEPT. OF COMM. BIBLIOGRAPHIC DATA SHEET *(See instructions)* | 1. PUBLICATION OR REPORT NO. NBSIR 86-3300 | 2. Performing Organ. Report No. | 3. Publication Date February 1987 |
|---|---|---|---|

**4. TITLE AND SUBTITLE**

STOVE:    A Predictive Model for Heat Transfer from Solid-Fuel Appliances

**5. AUTHOR(S)**

Richard D. Peacock and Richard A. Dipert

| 6. PERFORMING ORGANIZATION *(If joint or other than NBS, see instructions)* National Bureau of Standards Department of Commerce Gaithersburg, MD   20899 | 7. Contract/Grant No. |
|---|---|
| | 8. Type of Report & Period Covered |

**9. SPONSORING ORGANIZATION NAME AND COMPLETE ADDRESS *(Street, City, State, ZIP)***

**10. SUPPLEMENTARY NOTES**

☐ Document describes a computer program; SF-185, FIPS Software Summary, is attached.

**11. ABSTRACT *(A 200-word or less factual summary of most significant information. If document includes a significant bibliography or literature survey, mention it here)***

A computer implementation of a model to predict temperatures on wall and wall protector surfaces exposed to the heating of an appliance such as a solid fuel heating appliance is described.  A steady state heat transfer model with flexibility to describe a generalized method of protection for a combustible wall surface is presented along with a computer program implementing the model.  Good agreement was found comparing the model predictions with data previously collected during full scale experiments conducted to evaluate the effectiveness of generic methods of wall protection in reducing temperatures on combustible wall surfaces.  Extensive references of research related to solid fuel heating safety are included.

**12. KEY WORDS *(Six to twelve entries; alphabetical order; capitalize only proper names; and separate key words by semicolons)***

chimneys; fire models; fire safety; fire tests; flues; heat transfer; heating equipment; literature reviews; radiant energy; stoves; wood

| 13. AVAILABILITY | 14. NO. OF PRINTED PAGES |
|---|---|
| ☒ Unlimited | |
| ☐ For Official Distribution. Do Not Release to NTIS | 66 |
| ☐ Order From Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402. | 15. Price |
| ☒ Order From National Technical Information Service (NTIS), Springfield, VA. 22161 | $ 13.95 |

USCOMM-DC 6043-P80